

JABSCO IMPELLER IDENTIFICATION GUIDE

IMPELLER NUMBER	DRIVE MATERIAL	TYPE	NO. OF BLADES		DIAMETER		WIDTH		SHAFT DIA.		INSERT MATERIAL	REMARKS
					INCH	MM	INCH	MM	INCH	MM		
SILHOUETTE L												
3085-0001	Neoprene	7	10	2 1/4	57	1 1/4	31.5	5/8	16	BR		
18815-0005	Neoprene	6	10	2 1/4	57	1 1/4	31.5	5/8	12.7	BR	SS Extended Drive Cup (Sanitary)	
SILHOUETTE M												
920-0001	Neoprene	7	8	2 9/16	65	2	51	5/8	16	BR		
-0003	Nitrile	7	8	2 9/16	65	2	51	5/8	16	BR		
-0008†	Natl. Rub.	7	8	2 9/16	65	2	51	5/8	16	BR†	For Low Temp. to 27°F - Max. 120°F	
4598-0001	Neoprene	3	8	2 9/16	65	2	51	5/8	16	BR	Was D-12	
-0003	Nitrile	3	8	2 9/16	65	2	51	5/8	16	BR	Was D-12-37	
6056-0003	Nitrile	6	8	2 9/16	65	2	51	5/8	16	BR	SS Extended Drive Cup	
11979-0001	Neoprene	7	8	2 9/16	65	1 7/16	36.5	5/8	16	BR		
17018-0001	Neoprene	7	8	2 9/16	65	3	76.2	5/8	16	BR		
SILHOUETTE O												
836-0001	Neoprene	7	9	3 3/4	95	2 1/2	63	1	25	BR		
-0003	Nitrile	7	9	3 3/4	95	2 1/2	63	1	25	BR		
-0008†	Natl. Rub.	7	9	3 3/4	95	2 1/2	63	1	25	BR†		
6760-0001	Neoprene	7	9	3 3/4	95	3 1/2	88.9	1	25	BR		
-0003	Nitrile	7	9	3 3/4	95	3 1/2	88.9	1	25	BR		
-0008	Natl. Rub.	7	9	3 3/4	95	3 1/2	88.9	1	25	BR†		
SILHOUETTE Q												
17370-0001	Neoprene	5	12	3 3/4	95	3 1/2	88.9	1	25	PL		
17935-0001	Neoprene	7	12	3 3/4	95	2 1/2	63	1	25	BR	Alternative to 836-0001	
17936-0001*	Neoprene	7	12	3 3/4	95	3 1/2	88.9	1	25	BR	Alternative to 6760-0001	
21676-0003	Neoprene	7	12	3 3/4	95	3 1/2	88.9	1	25	BR	U.K. Equivalent to 17936-0001	
SILHOUETTE R												
17240-0001	Neoprene	7	9	4 5/8	118	3 1/2	88.9	1	25	BR		
18786-0001	Neoprene	5	9	4 5/8	118	3 1/2	88.9	1	25	PL		
18789-0001	Neoprene	7	9	4 5/8	118	3 1/2	88.9	1	25	BR	Replaces UK 17240-0001	
SILHOUETTE U												
2999-0001	Neoprene	7		13	5	127	4	101.6	1 1/2	38	BR	
SILHOUETTE W												
18838-0001	Neoprene	3	12	2 7/16	62	1 1/4	31.5	5/8	16	BR		
SILHOUETTE X												
18948-0001	Neoprene	3	12	2 9/16	65	1 5/8	41.4	5/8	16	BR		
SILHOUETTE Y												
17937-0001	Neoprene	7	10	2 9/16	65	2	51	5/8	15	BR	Replaces 920-0001	
-0003	Nitrile	7	10	2 9/16	65	2	51	5/8	16	BR		
17954-0001	Neoprene	4	10	2 9/16	65	2	51	3/4	19	BR	Mercuriser Replacement	
17956-0001	Neoprene	6	10	2 9/16	65	2	51	5/8	16	BR	SS Drive Cup, Replaces 6056-0001	
18327-0001	Neoprene	3	10	2 9/16	65	2	51	5/8	16	BR		
SILHOUETTE Z												
30919-0001	Neoprene	5	12	3 1/16	77	3	76.2		20	BR		
SILHOUETTE CC												
31130-0061	Neoprene	7	10	2 19/32	50.8	2 11/16	68.2	5/8	15	R	Mercuriser Replacement (HINO) (Replaces Quicksilver 47-831311350)	
SILHOUETTE GG												
18958-0001	Neoprene	3	12	3 1/4	95	2 57/64	73.4	25/32	20	BR		

INSERT MATERIAL: BR = Bronze, SS = Stainless Steel and PL = Plastic

† = For Low Temp. to 27°F Max. 120°F

* = The 17936-0001 impeller may be used to replace an English Model 21676-0001.