

WASHDOWN AND LIVEWELL

JABSCO



Washdown / Livewell

3.5 - 4.3 GPM, 50 PSI JABSCO WASHDOWN/LIVEWELL PUMPS

The Jabsco 32700 and 32605 series washdown pumps deliver an impressive 50 psi and up to 5.0 gpm. Its heavy duty low amperage motor with special waterproof coating and sealed pressure switch offer maximum corrosion protection in harsh environment installations. The motor is rated for continuous duty. This series is also suitable for dual washdown/baitwell duty. See page 157 for service parts.

Model Number	Max GPM	Volts	Amps at:		Inlet / Outlet	Dimensions (H x W x L)
			10 PSI	40 PSI		
JA 32605-0092	3.5	12 vdc	5.0	9.0	3/4" Barb and 3/4" GHT	4 1/16" x 3 1/2" x 8 5/8"
JA 32605-0094	3.5	24 vdc	3.0	6.0	3/4" Barb and 3/4" GHT	4 1/16" x 3 1/2" x 8 5/8"
JA 32700-0092	4.3	12 vdc	6.0	10.0	3/4" Barb and 3/4" GHT	3 1/2" x 3 7/8" x 9 1/2"
JA 32700-0094	4.3	24 vdc	3.0	5.0	3/4" Barb and 3/4" GHT	3 1/2" x 3 7/8" x 9 1/2"

FLOJET



Washdown

3.5 - 4.5 GPM, 40 PSI FLOJET WASHDOWN PUMPS

The Flojet automatic high velocity deck and anchor washdown pump will deliver up to 4.5 gpm and 40 psi. Models with the "L" suffix include a state of the art washdown nozzle with swivel disconnect check valve. See page 160 for service parts.

Model Number	Max GPM	Volts	Amps at 10 PSI	Inlet / Outlet	Includes Nozzle	Dimensions (H x W x L)
FJ 04325-143L	4.5	12 vdc	6.0	3/4" Barb and 3/4" GHT	Yes	3.9" x 4.2" x 10.1"
FJ 04325-343	4.5	24 vdc	3.0	3/4" Barb and 3/4" GHT	No	3.9" x 4.2" x 10.1"
FJ 04325-443	4.5	32 vdc	2.0	3/4" Barb and 3/4" GHT	No	3.75" x 6.3" x 9.9"
FJ 04305-144	3.5	12 vdc	5.0	3/4" Barb and 3/4" GHT	No	3.75" x 6.3" x 8.6"
FJ 04305-144L	3.5	12 vdc	5.0	3/4" Barb and 3/4" GHT	Yes	3.75" x 6.3" x 8.6"

SHURFLO



Pro Baitmaster

4.0 GPM, 45 PSI SHURFLO WASHDOWN/LIVEWELL PUMPS

The Shurflo "Pro Baitmaster" is excellent for livewell or washdown applications in harsh marine environments. Its seamless motor shell and sealed demand switch protect the pump from splashed liquids. It is self-priming, continuous duty and can run dry without damage. See page 170 for service parts.

Model Number	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 4901-7212	4.0	24 vdc	4.5	45	1/2" MPT and 3/4" Barb	5.0" x 5.5" x 9.25"

GROCO



Washdown

7 - 11 GPM, 50 PSI GROCO WASHDOWN PUMPS

The Groco C-60 series utilizes the dependable vane principle to deliver a smooth, high-pressure flow of salt or fresh water. Each pump comes with a 35 psi waterproof pressure switch, check valve, and washdown nozzle. The Groco PJRW and PSRW washdown pumps take advantage of the high-pressure lobe design of the popular Paragon water system pump series to deliver up to 11 gpm and up to 50 psi. This series is typically controlled with a foot or panel switch. It does not come with a demand pressure switch. (Use the Paragon series on page 14 for applications where a pressure switch is desired.) See page 166 and 167 for service parts.

Model Number	Max GPM	Volts	Max PSI	Breaker Size	Inlet	Outlet	Dimensions (H x W x L)
GC C-60 24V	7.5	24 vdc	35	20 Amps	1/2" FPT or 3/4" GHT	3/4" FPT	3.5" x 9.5" x 8.25"
GC PJRW 12V	7.0	12 vdc	50	30 Amps	3/4" FPT	3/4" FPT	4.5" x 8.25" x 8.25"
GC PSRW 12V	11	12 vdc	50	50 Amps	3/4" FPT	3/4" FPT	8.25" x 5.5" x 20.5"