

4.5 - 6 GPM, 70 PSI “HOT SHOT” WASHDOWN PUMPS

With the new “Hotshot” Series pumps, Jabsco now offers a complete range of washdown pumps from 4 - 7 gpm. Jabsco didn’t hold anything back. The sealed pressure switch and co-injected molded diaphragm eliminate leak paths. Large heavy duty brushes extend the motor life 50% longer than existing Par-MAX pumps. An ergonomically designed nozzle, Pumpguard strainer and noise dampening rubber mounts come standard with the pump. Quick disconnect ports allow for easy installation.

Series	Volts	Max GPM	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
JA 82405-Series	12 or 24vdc	4	70	3/4" Hose Barb	4.72" x 5.09" x 9.91"
JA 82505-Series	12 or 24vdc	5	70	3/4" Hose Barb	4.72" x 5.09" x 10.6"
JA 82605-Series	12 or 24vdc	6	70	3/4" Hose Barb	4.72" x 5.09" x 10.6"



7 GPM, 80 PSI ULTRA “PAR-MAX” WASHDOWN KIT

Jabsco’s new “Par-MAX 7” pump delivers an impressive 7 gpm and up to 80 psi. Its robust design offers a long life sealed motor, corrosion resistance and run dry capability. With complete instructions and an included main breaker, this washdown system can be installed on almost any size boat. The 52700 pump kit includes Pumpguard intake strainer, pressure nozzle, and port fittings. The 52900 pump kit includes the same as the 52700 with an added hose coil.

Model Number	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
52700-0092	7	12 vdc	28	80	1/2" or 3/4" Barb	6.25" x 6.11" x 10.15"
52700-0094	7	24 vdc	14	80	1/2" or 3/4" Barb	6.25" x 6.11" x 10.15"
52900-0092	7	12 vdc	28	80	1/2" or 3/4" Barb	6.25" x 6.11" x 10.15"
52900-0094	7	24 vdc	14	80	1/2" or 3/4" Barb	6.25" x 6.11" x 10.15"



3.5 - 5.2 GPM, 70 PSI “AQUA-JET” WASHDOWN PUMPS

The “Aqua Jet” 5 chambered diaphragm pumps by Johnson deliver up to 5.2 gpm and 70 psi. They will prime up to 6 feet and come complete with intake strainer, spray nozzle and 1/2" barbed fittings.

Model Number	Max GPM	Volts	Fuse Size	Inlet/Outlet	Dimensions (H x W x L)
JS 10-13399-03	3.5	12 vdc	15A	1/2" MPT and 3/4" Barb	4.57" x 8.25" x 9.31"
JS 10-13399-04	3.5	24 vdc	8A	1/2" MPT and 3/4" Barb	4.57" x 8.25" x 9.31"
JS 10-13407-07	5.2	12 vdc	20A	1/2" MPT and 3/4" Barb	4.33" x 8.43" x 9.46"
JS 10-13407-08	5.2	24 vdc	10A	1/2" MPT and 3/4" Barb	4.33" x 8.43" x 9.46"



2 - 5.5 GPM, 45 PSI “BLASTER” WASHDOWN PUMPS

The “Blaster” and “ProBlaster” 3 and 4 chamber diaphragm pumps by Shurflo deliver up to 4.0 gpm and 45 psi. For more flow there is the “Extreme Problaster” at 5.5 gpm and 45 psi. The “Blaster” pump series is constructed with a corrosion resistant coated seamless motor shell and sealed switch to provide protection against harsh marine environments. See page 170 for service parts.

Model Number	Max GPM	Volts	Max Amps	Inlet/Outlet	Dimensions (H x W x L)
SF 2901-6213	2.0	12 vdc	4	1/2" MPT and 3/4" Barb	4.6" x 5.0" x 7.6"
SF 3901-2214	3.5	12 vdc	6	1/2" MPT and 3/4" Barb	5" x 4.6" x 7.6"
SF 3901-3214	3.5	24 vdc	3	1/2" MPT and 3/4" Barb	5" x 4.6" x 7.6"
SF 4901-4282	4.0	12 vdc	10	1/2" MPT and 3/4" Barb	5.4" x 5.3" x 8.3"
SF 4901-5282	4.0	24 vdc	5	1/2" MPT and 3/4" Barb	5.4" x 5.3" x 8.3"
SF 5901-2212	5.5	12 vdc	14	1/2" MPT	5" x 5.5" x 9.25"
SF 5901-3212	5.5	24 vdc	6	1/2" MPT	5" x 5.5" x 9.25"
SF 5901-4212	5.5	32 vdc	5	1/2" MPT	5" x 5.5" x 9.25"

