

# LIVEWELL AND LOW PRESSURE WASHDOWN

## PRIMETIME



Stainless Self-Primer

### 3/4" 316SS SELF-PRIMER IN AC AND DC OR HYDRAULIC DRIVE

The "Primetime" self-primer will not air-lock. It is ideal for an installation that is prone to air-lock or requires a suction lift of up to 6 feet. This rugged cast 316 stainless steel pump comes equipped with a carbon/ceramic mechanical seal, 3/4" x 3/4" fpt ports and solid 316 stainless steel impeller. 115/230v versions come with a 6' cord with plug.

Model Number	Hz	Port Size	GPH at Feet of Head					Max Head
			5'	10'	15'	20'	25'	
DP Primetime 115/230v	50/60	3/4" FPT	1260	1110	900	570	300	24'
DP Primetime 12v	DC	3/4" FPT	1110	820	510	-	-	18.5'
DP Primetime 24v	DC	3/4" FPT	1110	820	510	-	-	18.5'
DP Hyd-PT	Hyd	3/4" FPT				*see note		52'

\*Hydraulic performance varies by hydraulic oil flow and pressure.

## MP / OBERDORFER



316SS and Bronze

### 3/4" 316SS AND BRONZE RECIRCULATORS IN AC AND DC

Oberdorfer and MP recirculators require flooded suction and are available in AC and DC voltages. The MP series is 316 stainless steel and comes standard with a Viton mechanical seal. The Oberdorfer series is constructed of bronze and comes with a Buna lip or mechanical seal. See page 154 for Oberdorfer service parts.

Model Number	Brand	Volts	Hz	GPM at Feet of Head			Max Head	Seal Type
				0'	5'	10'		
OB 172B-B26	Oberdorfer	115 vac	50/60	18	15	10	14'	Mechanical
OB 172B-B27	Oberdorfer	230 vac	50/60	18	15	10	14'	Mechanical
OB 172B-Series	Oberdorfer	12, 24 or 32 vdc		20	14	6	14'	Mechanical
OB 170M-Series	Oberdorfer	12, 24 or 32 vdc		20	14	6	14'	Lip
MP FRX75	MP	12, 24 vdc / 115, 230 vac	60	26	26	26	28'	Mechanical
MP FRX50	MP	12, 24, 32 vdc / 115, 230 vac	60	12.5	12	7.5	19'	Mechanical

## GROCO



Submersible or Open-Air

### 3/4" SPLASH PROOF RECIRCULATORS IN 12, 24 AND 32 VDC

This unique pump series adds a submersible motor boot to Groco's successful flanged suction bronze recirculation pump line, creating a waterproof recirculator for wet or submerged environments. Groco's original recirculators are also available with their continuous duty non-submersible motors (listed below). All models come standard with a mechanical seal. See page 165 for service parts.

Model Number	Volts DC	Motor Enclosure	GPM at Feet of Head			Duty	Dimensions
			0'	5'	10'		
GC CP-20	12 or 24 vdc	Non-Submersible	17	11.7	7.3	Cont.	3.5" x 4.5" x 7.75"
GC CP-20-S	12 or 24 vdc	Submersible	17	11.7	7.3	Int.	3.5" x 4.5" x 8.75"

## JABSCO / SHERWOOD



Cyclone / Aqua Tiger

### 3/4" STAINLESS STEEL RECIRCULATORS IN 12 AND 24 VDC

These stainless centrifugals combine the corrosion resistance of a stainless steel housing and the long service life of a mechanical seal. Jabsco's Cyclone pump series has three variations: high flow (50840-series), high pressure (50860-series) and continuous duty (50850-series) with BSP ports. See page 153 for Jabsco service parts.

Model Number	Volts DC	Max Amps	GPM at Feet of Head			Max Head	Dimensions (H x W x L)
			0'	10'	25'		
SH COMSV012D	12	10.5	20	15.5	-	21'	4 1/2" x 4 1/2" x 7 3/8"
SH COMSV024D	24	7.8	20	15.5	-	21'	4 1/2" x 4 1/2" x 7 3/8"
JA 50840-0012	12	9	29	10	-	20'	4 1/2" x 4 1/2" x 6 5/8"
JA 50840-0024	24	4.5	29	10	-	20'	4 1/2" x 4 1/2" x 6 5/8"
JA 50860-0012	12	21	21.1	18.5	12	43.5'	4 1/2" x 4 1/2" x 6 5/8"
JA 50860-0024	24	10.5	21.1	18.5	12	43.5'	4 1/4" x 4 1/2" x 6 5/8"
JA 50850-0012	12	5.2	13.7	5.5	-	20'	4 1/4" x 3 1/2" x 6 1/4"
JA 50850-0024	24	2.6	13.7	5.5	-	20'	4 1/4" x 3 1/2" x 6 1/4"