

LIVEWELL AND LOW PRESSURE WASHDOWN

12 VDC DUAL PORT FOR WASHDOWN PUMP ATTACHMENT

Both series of these unique pumps include a separate 1/2" fpt suction port that allows the attachment of a self-priming high-pressure washdown pump (see page 20 and 21). The Shurflo "Sentry" magnetic drive series is sealless and will not air-lock. Rule utilizes their proven direct drive design to provide a dependable and economical solution.

Model Number	Brand	GPH	Suction / Discharge	Amp Draw
SF 1700-001-030	Shurflo	500	3/4" MPT / 3/4" Male Barb	1.5
SF 1700-011-030	Shurflo	800	3/4" MPT / 3/4" Male Barb	2.75
SF 1700-021-030	Shurflo	1100	3/4" MPT / 1 1/8" Barb	3.75
RU 401FC	Rule	500	3/4" MPT / 3/4" Barb	2
RU 403FC	Rule	800	3/4" MPT / 3/4" Barb	2.8
RU 405FC	Rule	1100	1 1/8" MPT / 1/8" Barb	3.3



12 VDC THRU-HULL MOUNTED LIVEWELL PUMPS

Rule pumps are available in straight or angled thru-hull mounting to fit in the tightest bilge. Both mounting types are available in Rule's original or replaceable cartridge type configuration. The cartridge series allows for quick motor replacement without disturbing the thru-hull mounting.

Model Number	Thru-Hull Angle	GPH	Replacement Motor Cartridge	Suction / Discharge	Fuse Size
RU 401C	Angled	500	45DR	3/4" MPT / 3/4" Barb	2.5
RU 401STC	Straight	500	45DR	3/4" MPT / 3/4" Barb	2.5
RU 403C	Angled	800	46DR	3/4" MPT / 3/4" Barb	5
RU 403STC	Straight	800	46DR	3/4" MPT / 3/4" Barb	5
RU 405C	Angled	1100	47DR	1 1/8" MPT / 1 1/8" Barb	6
RU 405STC	Straight	1100	47DR	1 1/8" MPT / 1 1/8" Barb	6



12 - 32 VDC HIGH CAPACITY BAITWELL/WASHDOWN PUMPS

These Rule pumps offer high flows for large baitwells, commercial livewells, and low-pressure washdown applications. The 209FDP mounts directly on a thru-hull with its 1" mpt suction port. The 209B model features a bronze base, anti-airlock feature and a heavy duty long life motor. The 17A - 19A series utilizes 1 1/2" slip-on ports to connect into your system.

Model Number	Volts	GPH	Suction / Discharge	Amp Draw
RU 17A	12 vdc	3800	1 1/2" Barb / 1 1/2" Barb	15.5
RU 18A	24 vdc	3700	1 1/2" Barb / 1 1/2" Barb	6.9
RU 19A	32 vdc	3700	1 1/2" Barb / 1 1/2" Barb	5.0
RU 209B	12 vdc	1600	1" MPT / 1 1/8" Barb	4.8
RU 209FDP	12 vdc	1600	1" MPT / 1 1/8" Barb	4.8



12 VDC DUAL PORT FOR WASHDOWN PUMP ATTACHMENTS

These Johnson pumps offer the convenience of using one intake for both livewell and raw water washdown pump. The 3/4" tapered inlet connects directly to the seacock and the upper outlet port provides a continuous flow of water through the 3/4" discharge to the livewell while the lower inlet port connects to the washdown pump through either a 1/2" or 3/4" port. New high pressure inlet seal easily handles the higher pressures created by high speed pick ups commonly used.

Model Number	GPH	Suction Discharge	Fuse Size
JS 48503	500	3/4" MPT / 3/4" Male Barb	5
JS 48703	750	3/4" MPT / 3/4" Male Barb	5
JS 48903	1000	3/4" MPT / 3/4" Male Barb	5
JS 48103	1250	3/4" MPT / 3/4" Male Barb	5

* 1 1/8" discharge to livewell. Does not include Dura-Port.

