

SELF-PRIMING SHOWER SUMP PUMPS

3.5 GPM JABSCO 32601 SERIES SHOWER PUMP

Jabco's 32601 series shower and gray water pump comes standard with a continuous duty DC motor with a waterproof coating for harsh bilge environments. It can be operated with a manual on/off switch or automatic level control (see page 32), and will self-prime to 10 feet. The pump comes with $\frac{3}{4}$ " barbed ports and a $\frac{3}{4}$ " suction strainer. See page 157 for service parts.

Model Number	Volts	Amps at 10 psi	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 32601-0092	12 vdc	5	3.5	$\frac{3}{4}$ " Barb	4.1" x 4.2" x 7.7"
JA 32601-0094	24 vdc	3	3.5	$\frac{3}{4}$ " Barb	4.1" x 4.2" x 7.7"

JABSCO



32601 Series

3.3 GPM FLOJET 4105 SERIES SHOWER PUMP

The Flojet 4105 shower and gray water pump will lift water up to 10 feet and will not be damaged by running dry. It can be operated with a manual on/off switch or automatic level control (see page 32) and comes standard with $\frac{1}{2}$ " barbed ports. However, $\frac{3}{4}$ " barbed port fittings (page 64) and suction strainers (page 65) are available separately. See page 160 for service parts.

Model Number	Volts	Amps at 10 psi	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
FJ 04105-143	12 vdc	3.6	3.3	$\frac{1}{2}$ " Barb	3.9" x 4.2" x 7.7"
FJ 04105-343	24 vdc	1.8	3.3	$\frac{1}{2}$ " Barb	3.9" x 4.2" x 7.7"

FLOJET



4105 Series

4.2 GPM JABSCO 50880 SERIES SHOWER PUMP

Jabco's 50880 series shower and gray water pump features a unique 360° rotating head for flexible installation. This pump self-priming up to ten feet and will run dry without damage. No-clog, filterless design means easy maintenance. Complies with USCG 183.410 and ISO 8846 Marine (Ignition Protection).

Model Number	Volts	Max Amps	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 50880-1000	12 vdc	8	4.2	$\frac{3}{4}$ " Barb	4.4" x 5.9" x 11.7"
JA 50880-1100	24 vdc	2.5	4.2	$\frac{3}{4}$ " Barb	4.4" x 5.9" x 11.7"

JABSCO



50880 Series

3.5 GPM WHALE GULPER 220 SHOWER PUMP

The Whale Gulper 220 shower and gray water pump incorporates inlet and outlet duckbill valves that are specifically designed to pump wastewater without clogging. This eliminates the need for a suction filter. Each pump can be operated with a manual on/off switch or automatic level control (see page 32), will self-prime to 12 feet vertically, run dry without damage and come with $\frac{3}{4}$ " barbed ports that can be repositioned in any in-line direction by loosening the body clamp ring. (Repair Kit = IM AK1550)

Model Number	Volts	Amp Draw	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
WH BP1552	12 vdc	10	3.5	$\frac{3}{4}$ " Barb	4 $\frac{5}{8}$ " x 6 $\frac{3}{4}$ " x 10 $\frac{3}{4}$ "
WH BP1554	24 vdc	6	3.5	$\frac{3}{4}$ " Barb	4 $\frac{5}{8}$ " x 6 $\frac{3}{4}$ " x 10 $\frac{3}{4}$ "

WHALE



Gulper 220 Series