

SUBMERSIBLE BILGE PUMPS

JOHNSON



750 4000
Mayfair Interchange

525 - 2600 GPH PUMPS IN 12 VDC AND 24 VDC

Johnson bilge pumps feature rugged design using high quality materials. The 525-2600 gph models have cartridge style motors for easy cleaning. The heavy duty 1600 - 2600 gph pumps feature liquid cooled motors with double ball bearings and either lip seals (1600) or extended life mechanical shaft seals (2200 and 4000).

Model Number	Mayfair Model	GPH at 3 Ft	Volts	Amps	Hose Dia	Dimensions (H x W x L)
JS 32503	32502	525	12	2.5	3/4"	4 1/2" x 2 3/4" x 4"
JS 32703	32702	700	12	3	3/4"	4 1/2" x 2 3/4" x 4"
JS 32903	32102	800	12	3.2	3/4"	4 1/2" x 2 3/4" x 4"
JS 42123	42122	952	12	3	1 1/8"	4 1/2" x 2 3/4" x 4"
JS 16004-00		1550	12	7	1 1/8", 1 1/4"	6" x 4.25" x 6 1/2"
JS 22004		1900	12	7.5	1 1/8", 1 1/4"	7" x 4" x 6 1/2"
JS 22084		1900	24	4.5	1 1/8", 1 1/4"	7" x 4" x 6 1/2"
JS 40004		2600	12	15	1 1/2", 2"	8 1/2" x 4 3/4" x 6 1/2"
JS 40084		2600	24	7.5	1 1/2", 2"	8 1/2" x 4 3/4" x 6 1/2"

SHURFLO



Magnetic Drive Series

CARTRIDGE STYLE BILGE PUMPS 380-2000 GPH

The Shurflo series bilge pumps feature anti-airlock design. Pumps are made of high-density nylon housing, tinned copper wire and continuous duty motors. Removable cartridge design allows easy cleaning or replacement. Three year warranty.

Model Number	GPH at 0 Feet	Volts	Max Amps	Hose Dia.	Dimensions (H x W x L)
SF 355-020-10	380	12 vdc	1.7	3/4"	4 1/4" x 2 3/8" x 3 3/4"
SF 355-010-10	500	12 vdc	1.8	3/4"	4 1/4" x 2 3/8" x 3 3/4"
SF 355-110-10	700	12 vdc	3.2	3/4"	4 1/4" x 2 3/8" x 3 3/4"
SF 355-100-10	1000	12 vdc	3.2	1 1/8"	4 1/4" x 2 3/8" x 3 3/4"
SF 358-000-10	1500	12 vdc	8	1 1/8"	6" x 5" x 7 1/4"
SF 358-100-10	1500	24 vdc	4	1 1/8"	6" x 5" x 7 1/4"
SF 358-010-10	2000	12 vdc	10	1 1/8"	6" x 5" x 7 1/4"
SF 358-110-10	2000	24 vdc	5	1 1/8"	6" x 5" x 7 1/4"

WHALE



Super Sub

LOW PROFILE AUTOMATIC BILGE PUMP UP TO 1050 GPH

The new Whale Super Sub low profile automatic bilge pump is ideal for tight spaces, automatically senses bilge water level and switches on and off. No separate switch required. The pump has built in electric field sensor technology, contains no moving parts and is unaffected by wave motion. The pump can quickly be mounted vertically or horizontally. A unique simple to remove strainer makes cleaning quick and easy. Pump is environmentally friendly. Conforms to ISO 8849 and ISO 15083.

Model Number	GPH at 0 Feet	Volts	Max Amps	Hose Dia.	Dimensions (H x W x L)
WH SS5212	650	12 vdc	3	3/4"	2 1/8" X 2 1/8" X 8 3/8"
WH SS1212	1050	12 vdc	4.3	1 1/8"	3" X 2 1/8" X 9 1/2"
WH SS1224	1050	24 vdc	2	1 1/8"	3" X 2 1/8" X 9 1/2"

WHALE



Orca Series

500 - 3000 GPH COMPACT BILGE PUMPS IN 12 AND 24 VDC

Whale's new Orca bilge pump is both compact and powerful. The large filter base ensures that the maximum surface area is exposed to bilge water. Installation is easy with multiple wire locations. Cleaning is a snap by just pulling the cover up. Low amp draw means longer battery life. Meets ISO8849 marine standard.

Model Number	GPH at 0 Feet	Volts	Max Amps	Hose Dia.	Dimensions (H x W x L)
WH BE0500	500	12 vdc	1.5	3/4"	3.3" x 4" x 3"
WH BE0950	950	12 vdc	3.5	1 1/8"	4 1/4" x 5 1/4" x 4"
WH BE1450	1300	12 vdc	5.0	1 1/8"	5" x 6 3/5" x 4 4/5"
WH BE1454	1300	24 vdc	2.5	1 1/8"	5" x 6 3/5" x 4 4/5"
WH BE2002	2000	12 vdc	10	1 1/8"	6 1/2" x 4 3/4"
WH BE2004	2000	24 vdc	5	1 1/8"	6 1/2" x 4 3/4"
WH BE3002	3000	12 vdc	18	1 1/4"	7 5/8" x 5 1/8"
WH BE3004	3000	24 vdc	9	1 1/4"	7 5/8" x 5 1/8"