

JABSCO OIL CHANGE / DIESEL TRANSFER

REVERSIBLE VANE FOR OIL CHANGE / DIESEL TRANSFER

These Jabsco pumps utilize the proven vane pump design, which is ideally suited for oil and diesel transfer. Each pump comes equipped with a three-way reversible switch that allows the removal of the old oil and the filling of the new. These pumps can be installed with a manifold (as shown on the bottom of page 40) to create a complete oil change system for your vessel. Each pump has 1/2" FPT internal ports with 1" external hose barbs. The service kit includes the vanes, rotor, o-ring, and seal and can be ordered under the number JA 90200-0001.

Model Number	Volts	Max GPM	Amp Draw	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 18680-1000	12 vdc	6	8	1/2" FPT and 1" Slip-On	3 3/8" x 4 3/4" x 8"

JABSCO



Reversible Vane Design

VANE PUMPS FOR OIL CHANGE / DIESEL TRANSFER PUMPS

These Jabsco pumps are ideal for oil change or diesel transfer where a reversing switch is not required. Each pump has 1/2" fpt internal ports with 1" external hose barbs. The service kit includes the vanes, rotor, o-ring and seal and can be ordered under the number JA 90200-0001.

Model Number	Volts	Max GPM	Amp Draw	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 18680-0920	12 vdc	6	8	1/2" FPT and 1" Slip-On	3 3/8" x 4 3/4" x 7 1/8"
JA 18680-0940	24 vdc	6	5	1/2" FPT and 1" Slip-On	3 3/8" x 4 3/4" x 7 1/8"

JABSCO



Continuous Duty Vane Design

JUNIOR GEAR PUPPY FOR OIL CHANGE/DIESEL TRANSFER

Jabsco's new Junior Gear Puppy was designed for oil change and diesel transfer. They are self-priming to 3 feet, transfer up to 3.5 gpm and suitable for oils up to 150 centistokes viscosity. They come with 1/2" hose barb ports, suction strainer and a 15 minute duty dc motor.

Model Number	Volts	Max GPM	Fuse Size	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 23220-2012	12V	3.5	10 amps	1/2" Barb	3" x 6.5" x 5.5"
JA 23220-2024	24V	3.5	5 amps	1/2" Barb	3" x 6.5" x 5.5"

JABSCO



Junior Gear Puppy

GEAR PUPPY FOR OIL CHANGE/DIESEL TRANSFER

Jabsco's new Gear Puppy was designed for oil change and diesel transfer. They are self-priming to 3 feet, transfer up to 6.5 gpm and suitable for oils up to 150 centistokes viscosity. They come with 5/8" hose barb ports, suction strainer and a 15 minute duty dc motor.

Model Number	Volts	Max GPM	Fuse Size	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 23230-2012	12V	6.5	15 amps	5/8" Barb	4" x 7" x 7"
JA 23230-2024	24V	6.5	7.5 amps	5/8" Barb	4" x 7" x 7"

JABSCO



Gear Puppy