

PACER/AMT



**Polypropylene, Ryton,
Nylon, Polyester & Halar**

**PISTON STYLE IN MULTIPLE MATERIALS,
4 TO 6 STROKES PER GALLON**

Pacer and AMT manufacture similar piston style drum pumps out of various materials suitable for a wide variety of oils, detergents, lubricants, lacquers, acids, caustics, alcohols and other liquids compatible with their respective construction.

Brand and Model Series	Housing Material	Other Materials in Contact with Solution	Number of Strokes per Gallon
Pacer HP Series	Polyester	316SS and Viton or EPDM	4
Pacer HR Series	Ryton	316SS and Viton or EPDM	4
Pacer HH Series	Hylar	316SS and Viton or EPDM	4
AMT 4660-99	Polypropylene	316SS, Viton, Teflon & Nitrile	6
AMT 4661-99	Nylon	316SS, Viton, Teflon & Nitrile	6

AMT



316SS, Polypropylene & Ryton

**ROTARY STYLE IN 316SS, RYTON & POLYPROPYLENE,
23 ROTATIONS PER GALLON**

AMT manufactures these rotary pumps for multiple applications. The 316SS is designed for use with acid, acetones, alcohols, trichloroethylene, solvents, photographic chemicals and ketones. The Ryton pump is typically used with aggressive chemicals including many esters, ketones, alcohols and hydrocarbons. The polypropylene model handles most organic acids, alcohols and other water-soluble inorganic chemicals. Before using any of the above pumps, verify your chemical is compatible with ALL the pump's components.

Model Number	Housing Material	Other Materials in Contact with Solution	Max Temp	Number of Rotations per Gallon
AMT 5270-98	316SS	Teflon and Carbon	200° F	23
AMT 4940-99	Ryton	316SS, Viton and Carbon	180° F	23
AMT 4945-99	Polypropylene	316SS, Viton and Phenolic	180° F	23

AMT/JABSCO



Stainless & Brass

**CYLINDER "PISTON" STYLE IN 316SS & BRASS,
7 TO 40 STOKES PER GALLON**

AMT and Jabsco produce versatile cylinder style piston pumps in 316SS and brass. The 316SS AMT pump will handle many acids, toluene, solvents, acetone, trichloroethylene and other liquids compatible with its materials. The Jabsco series is manufactured of brass and oil resistant rubbers to handle water, oils, diesel and other liquids compatible with their materials.

Brand and Model Series	Housing Material	Other Materials in Contact with Solution	Number of Strokes per Gallon
AMT 4840-98	316SS	Teflon parts	16
Jabsco 34060	Brass	Oil resistant rubber	40
Jabsco 33799	Brass	Oil resistant rubber	26
Jabsco 33760	Brass	Oil resistant rubber	15
Jabsco 33745	Brass	Oil resistant rubber	7

BOSWORTH



Delrin

**DIAPHRAGM PUMP IN DELRIN,
10 TO 15 GALLONS PER MINUTE**

Bosworth manufactures an economical self-priming diaphragm pump that will lift up to 12 feet, discharge up to 12 feet vertically and handle solids. The rubber elastomers are available in Buna, Neoprene, Viton, Silicone and EPDM. A food grade version is displayed on page 105.

Model Number	Housing Material	Elastomer Options	Gallons Per Minute
400 Series	Delrin	Buna, Neoprene, Viton, Silicon and EPDM	10
500 Series	Delrin	Buna, Neoprene, Viton, Silicon and EPDM	15