

SIMER



Economy Series

UP TO 85 GPM, 25 TDH ECONOMICAL PLASTIC

Simer plastic submersible pumps are available with or without an automatic switch, withstand temperatures to 120° F, and are supplied with an 8 foot electric cord. Sizes range from 1/4 to 1/2 hp and come with a 1 1/4" or 1 1/2" MPT discharge port with garden hose adapter.

PUMP MODEL	HP	VOLTAGE	GPM AT FEET OF HEAD					DISCHARGE PORT
			0'	5'	10'	15'	20'	
SM 2305	1/6	115 vac	21	19	17	14	8	1 1/4" FPT
SM 2355	1/3	115 vac	44	37	34	26	19	1 1/4" FPT
SM 2380	1/2	115 vac	85	81	77	41	22	1 1/2" FPT
SM 3010	1/6	12 vdc	23	20	18	14	10	1 1/4" FPT

LITTLE GIANT



Sump & Effluent Series

UP TO 5000 GPH, 26 TDH CAST IRON & BRONZE

Little Giant submersible pumps come standard in cast iron/plastic construction. The 8 and 12 series are also available in bronze construction. Each size is available with or without an automatic switch, withstand temperatures peaking to 120° F, and are supplied with an 8 to 25 foot electric cord. Sizes range from 3/10 to 1/2 hp and come with a 1 1/4" or 1 1/2" FPT discharge port.

PUMP MODEL	HP	VOLTS AC	GPH AT FEET OF HEAD				SHUTOFF	DISCHARGE PORT
			5'	10'	15'	SHUTOFF		
LG 6 SERIES	3/10	115	2750	1750	750	18.0'	1 1/4" FPT	
LG 6E SERIES	1/3	115	3000	2500	1600	20.0'	1 1/2" FPT	
LG 8 SERIES	4/10	115	3250	2500	1550	22.9'	1 1/2" FPT	
LG 10 SERIES	1/2	115	4200	3800	2700	23.0'	1 1/2" FPT	
LG 12 SERIES	1/2	115	5000	4000	3000	26.0'	1 1/2" FPT	

HYDROMATIC



Sump & Effluent Series

UP TO 3600 GPH, 25 TDH CAST IRON & BRONZE

Hydromatic submersible pumps come standard in cast iron/plastic construction. The OSP33A1 AB is constructed in bronze with a diaphragm float switch. The SD series also is equipped with a diaphragm switch, while the SW series utilizes a float switch. Each model can withstand temperatures to 120° F, are supplied with a 10 foot (20 foot optional) electric cord, have a 1 1/2" FPT discharge port, and come in 1/4 or 1/3 hp.

MODEL	HP	VOLTS AC	GALLONS PER HOUR @ FEET OF HEAD						SWITCH TYPE
			1'	5'	10'	15'	20'	25'	
HY SW25A1	1/4	115	2640	2580	2100	1500	750	—	Float
HY SD25A1	1/4	115	2640	2580	2100	1500	750	—	Diaphragm
HY SW33A1	1/3	115	2850	2760	2400	1920	1320	250	Float
HY SD33A1	1/3	115	2850	2760	2400	1920	1320	250	Diaphragm
HY OSP33A1 AB	1/3	115	3600	3500	3120	2520	1680	—	Diaphragm

OBERDORFER



Sump & Effluent Series

UP TO 4100 GPH, 32 TDH STAINLESS/BRONZE SUBMERSIBLES

Oberdorfer manufactures a unique automatic submersible with stainless motor and bronze pump components. The motor housing operates as the float switch. As the water level rises, the air filled housing floats up and actuates the switch. Likewise, as the water is evacuated, the housing descends and shuts off the pump. These pumps can withstand temperatures to 150° F, are supplied with a 10 foot electric cord, have a 1 1/4" FPT discharge port and come in 1/3 or 1/2 hp.

MODEL	HP	VOLTS AC	GALLONS PER HOUR @ FEET OF HEAD					DISCHARGE PORT	
			1'	5'	10'	15'	20'		
OB 3500S-F31	1/3	115	3650	3500	2700	1800	800	—	1-1/4"
OB 4100S-J27	1/2	115	4100	4000	3800	3400	2500	1500	1-1/4"