

- CONTENTS
- INDEX
- NEXT
- BACK
- HOME

UP TO 10' TDH, 205 GPH IN-PAN MOUNTING

This Little Giant pump is designed to mount in your existing pan. Its dimensions are 4 7/16" in height, 3 3/4" in width and 7 7/16" in length. The float switch activates with one inch of water depth and deactivates once the level is reduced to 1/2". The discharge port is 1/4" FPT and will accept 1/4" ID tube.

- 10 feet of vertical lift
- 1" cut-on, 1/2" cut-off
- 4 7/16 x 7 7/16" x 3 3/4"
- 6 foot power cord
- Epoxy coated aluminum housing
- Available in 115 and 230 vac

Model	Volts	Gallons Per Hour*				Max. Head	Dimensions (H x L x W)
		1'	3'	5'	7'		
LG 1-ABS	115V	205	180	145	95	10'	4 7/16" x 7 7/16" x 3 3/4"



UP TO 80 GPH, 20' TDH UPGRADED CONDENSATE PUMP

Little Giant has incorporated many new features into the VCMA series condensate pump making it suitable for high efficiency gas furnaces as well as standard condensate removal installations. The VCMA comes standard with added ventilation to prolong motor life, thermal overload protection, reversible tank cover for installation flexibility, elevated intake to reduce clogging, and optional safety switch. Other features include:

- 1/2 gal. ABS tank
- 6', 3 prong power cord
- 3 inlet drain holes
- Removable 3/8" barbed check valve

Model	Gallons Per Hour*					Max. Head	Dimensions (H x L x W)
	1'	4'	6'	8'	12'		
VCMA-15	65	53	45	34	14	15'	7" x 10 5/16" x 5"
VCMA-20	80	72	66	60	40	20'	7" x 10 5/16" x 5"



UP TO 450 GPH, 45' TDH LOW PROFILE AND STANDARD

Little Giant's standard line of condensate pumps start with their low profile VCC series to their high volume – high head VCL-45ULS model. All are suitable for high-efficiency gas furnaces as well as standard condensate removal installations. All models come standard with thermal overload protection, stainless steel shaft, galvanized steel tank cover, ABS tank, snap-action switch and a 6', three prong power cord.

Model	Gallons Per Hour*					Max. Head	Dimensions (H x L x W)
	1'	4'	6'	12'	20'		
VCC-20	80	72	66	40	-	20'	5 7/8" x 12" x 5"
VCL-14	200	175	157	50	-	14'	9 1/2" x 12" x 6"
VCL-24	270	255	240	170	130	24'	10 5/8" x 12" x 6"
VCL-45	450	440	430	380	345	45'	10 5/8" x 12" x 6"



UP TO 85 GPM, 130' TDH BOILER CONDENSATE

Burks GV series condensate return systems are a uniquely integrated pump/tank arrangement for commercial and industrial boilers. The heavy-duty tanks are standard in cast iron (fabricated steel optional). The pumps are cast iron/bronze fitted simplex and duplex systems that are available with float level switches and controls. The tanks come in 9, 14, 23 and 36 gallon sizes. Electrical choices are 115v/230v, 1ph or 230v/460v, 3ph with ODP, TEFC or XP enclosures.

Model	Gallons Per Minute				Max. Head	Max. Temp.
	25'	50'	75'	100'		
7V6-1 1/4	50	10	-	-	52'	225° F
10GV6-1 1/4	57	30	-	-	55'	225° F
15GV6-1 1/4	-	60	28	-	77'	225° F
20GV6-1 1/4	-	73	56	-	90'	225° F
30GV6-1 1/4	-	-	78	60	120'	225° F



*Based on pumping thru 1/4" I.D. tubing