

JABSCO IMPELLER IDENTIFICATION GUIDE



IMPELLER NUMBER	DRIVE MATERIAL	TYPE	NO. OF BLADES	Diameter		DIMENSIONS		Width		SHAFT DIA.		INSERT MATERIAL	REMARKS
				inch	mm	inch	mm	inch	mm	inch	mm		
SILHOUETTE L													
3085-0001	Neoprene	7	10	2-1/4	57	1-1/4	31.5	5/8	16	BR			
18815-0005	Neoprene	6	10	2-1/4	57	1-1/4	31.5	5/8	12.7	BR		SS Extended Drive Cup (Sanitary)	
SILHOUETTE M													
920-0001	Neoprene	7	8	2-9/16	65	2	51	5/8	16	BR			
-0003	Nitrile	7	8	2-9/16	65	2	51	5/8	16	BR			
-0008†	Natl. Rub.	7	8	2-9/16	65	2	51	5/8	16	BR†		For Low Temp. to 27°F - Max. 120°F	
4598-0001	Neoprene	3	8	2-9/16	65	2	51	5/8	16	BR		Was D-12	
-0003	Nitrile	3	8	2-9/16	65	2	51	5/8	16	BR		Was D-12-37	
6056-0003	Nitrile	6	8	2-9/16	65	2	51	5/8	16	BR		SS Extended Drive Cup	
11979-0001	Neoprene	7	8	2-9/16	65	1-7/16	36.5	5/8	16	BR			
17018-0001	Neoprene	7	8	2-9/16	65	3	76.2	5.8	16	BR			
SILHOUETTE O													
836-0001	Neoprene	7	9	3-3/4	95	2-1/2	63	1	25	BR			
-0003	Nitrile	7	9	3-3/4	95	2-1/2	63	1	25	BR			
-0008†	Natl. Rub.	7	9	3-3/4	95	2-1/2	63	1	25	BR†			
6760-0001	Neoprene	7	9	3-3/4	95	3-1/2	88.9	1	25	BR			
-0003	Nitrile	7	9	3-3/4	95	3-1/2	88.9	1	25	BR			
-0008	Natl. Rub.	7	9	3-3/4	95	3-1/2	88.9	1	25	BR†			
SILHOUETTE Q													
17370-0001	Neoprene	5	12	3-3/4	95	3-1/2	88.9	1	25	PL			
17935-0001	Neoprene	7	12	3-3/4	95	2-1/2	63	1	25	BR		Alternative to 836-0001	
17936-0001*	Neoprene	7	12	3-3/4	95	3-1/2	88.9	1	25	BR		Alternative to 6760-0001	
21676-0003	Neoprene	7	12	3-3/4	95	3-1/2	88.9	1	25	BR		U.K. Equivalent to 17936-0001	
SILHOUETTE R													
17240-0001	Neoprene	7	9	4-5/8	118	3-1/2	88.9	1	25	BR			
18786-0001	Neoprene	5	9	4-5/8	118	3-1/2	88.9	1	25	PL			
18789-0001	Neoprene	7	9	4-5/8	118	3-1/2	88.9	1	25	BR		Replaces UK 17240-0001	
SILHOUETTE U													
2999-0001	Neoprene	7	13	5	127	4	101.6	1-1/2	38	BR			
SILHOUETTE W													
18838-0001	Neoprene	3	12	2-7/16	62	1-1/4	31.5	5/8	16	BR		Replaces Sherwood 9959 Impeller	
SILHOUETTE X													
18948-0001	Neoprene	3	12	2-9/16	65	1-5/8	41.4	5/8	16	BR		Replaces Sherwood 10615 Impeller	
SILHOUETTE Y													
17937-0001	Neoprene	7	10	2-9/16	65	2	51	5/8	15	BR		Replaces 920-0001	
-0003	Nitrile	7	10	2-9/16	65	2	51	5/8	16	BR			
17954-0001	Neoprene	4	10	2-9/16	65	2	51	3/4	19	BR		Mercuriser Replacement	
17956-0001	Neoprene	6	10	2-9/16	65	2	51	5/8	16	BR		SS Drive Cup, Replaces 6056-0001	
18327-0001	Neoprene	3	10	2-9/16	65	2	51	5/8	16	BR		Replaces Sherwood 15000 Impeller	
SILHOUETTE Z													
30919-0001	Neoprene	5	12	3-1/16	77	3	76.2	20		BR			
SILHOUETTE CC													
31130-0061	Neoprene	7	10	2-19/32	50.8	2-11/16	68.2	5/8	15	R		Mercuriser Replacement (HINO) (Replaces Quicksilver 47-831311350)	
SILHOUETTE GG													
18958-0001	Neoprene	3	12	3-1/4	95	2-57/64	73.4	25/32	21	BR		Replaces Sherwood 17000 Impeller	

INSERT MATERIAL: BR = Bronze, SS = Stainless Steel & PL = Plastic

† = For Low Temp. to 27°F Max. 120°F

* = The 17936-0001 impeller may be used to replace an English Model 21676-0001.