

3/4" BRONZE SELF-PRIMER IN 12 VDC & 115 VAC

The Primo bronze self-priming centrifugal can prime up to 3 feet and pump up to 20 gpm. The self-priming feature also prevents air lock by enabling the pump to evacuate air from the suction line. It has a lightweight and compact design with 3/4" FPT ports and 12 vdc or 115 vac motor.

Model Number	Volts/ Amps	Hz	GPM @ Feet of Head			Max Head	Port Size
			0	5	10		
DP Primo 115V	115 vac	60	20	16.5	11.5	16	3/4" FPT
DP Primo 12V	12 vdc/10.5		17	14	8	14	3/4" FPT



3/4" BRONZE RECIRCULATORS IN AC & DC

These bronze centrifugal pumps by Oberdorfer and Jabsco are available with a mechanical or lip seal in 115 vac, 230 vac, 12 vdc, 24 vdc or 32 vdc. They are lightweight, compact and come standard with 3/4" FPT ports. See page 122 and 124 for Jabsco and Oberdorfer service parts.

Model Number	Brand	Volts/ Amps	Hz	GPM @ Feet of Head			Max Head	Seal Type
				0	5	10		
JA 18580-0000	Jabsco	115 vac	60	22	20	15	15	Lip
JA 18510-000X	Jabsco	12 or 24 vdc		20	15	7.5	12	Lip
JA 18510-002X	Jabsco	12 or 24 vdc		15	12	5.5	12	Mech.
OB 172B-B26	Oberdorfer	115 vac	50/60	18	15	10	14	Mech.
OB 172B-B27	Oberdorfer	230 vac	50/60	18	15	10	14	Mech.
OB 172B-Series	Oberdorfer	12, 24 or 32 vdc		20	14	6	14	Mech.
OB 170M-Series	Oberdorfer	12, 24 or 32 vdc		20	14	6	14	Lip



3/4" SPLASH PROOF RECIRCULATORS IN 12, 24 & 32 VDC

This unique pump series adds a submersible motor boot to Groco's successful bronze recirculation pump line creating a waterproof recirculator for wet or submerged environments. Groco's original recirculators are also available with their continuous duty non-submersible motors (listed below). All models come standard with a mechanical seal. See page 138 for service parts.

Model Number	Volts DC	Motor Enclosure	GPM @ Feet of Head			Duty	Dimensions
			0	5	10		
GC CP-20	12, 24 or 32	Non-Submersible	17	11.7	7.3	Cont.	3.5" x 4.5" x 7.75"
GC CP-20-S	12, 24 or 32	Submersible	17	11.7	7.3	Int.	3.5" x 4.5" x 8.75"
GC CP-5009	12, 24 or 32	Submersible	30	17	9	Cont.	4.5" x 4.5" x 9.5"



3/4" STAINLESS STEEL RECIRCULATOR IN 12 VDC

Sherwood's AT20SS recirculating pump combines the corrosion resistance of stainless steel, a high flow-head impeller, and a Viton mechanical seal to produce a superior pump. Mounted below the waterline, the AT20SS will deliver continuous flow for baitwell, refrigeration, or low-pressure washdown.

Model Number	Volts DC	Max. Amps	GPM @ Feet of Head			Max. Head	Dimensions (H x W x L)
			0	5	10		
SH AT20SS	12	5.5	20	18	15.5	21'	4 1/2" x 4 1/2" x 7 3/8"

