



RULE

360 - 8000 GPH PUMPS IN 12, 24 & 32 VDC

These traditional bilge pumps are activated by a panel or float switch purchased separately (see page 25 or 53). All models are totally submersible, ignition protected, and incorporate an anti-air lock feature.

Model No.	GPH at 0 TDH	Max. Head	Volts	Amps	Hose Dia.	Dimensions (H x W x L)
RU 174D	8000	27'	12 vdc	40	3"	7 1/4" x 12" x 4 7/8"
RU 56D	4000	26'	12 vdc	20	2"	7 3/4" x 4 7/8" x 4 7/8"
RU 14A	3700	25'	12 vdc	20	1 1/2"	7 1/4" x 4 7/8" x 4 7/8"
RU 16A	3700	25'	24 vdc	8	1 1/2"	7 1/4" x 4 7/8" x 4 7/8"
RU 15A	3700	25'	32 vdc	6	1 1/2"	7 1/4" x 4 7/8" x 4 7/8"
RU 10	2000	21'	12 vdc	12	1 1/8"	6" x 4 1/4" x 4 1/4"
RU 11	2000	21'	32 vdc	5	1 1/8"	6" x 4 1/4" x 4 1/4"
RU 12	2000	21'	24 vdc	6	1 1/8"	6" x 4 1/4" x 4 1/4"
RU 02	1500	12'	12 vdc	7	1 1/8"	6" x 4 1/4" x 4 1/4"
RU 27D	1100	12'	12 vdc	5	1 1/8"	3 7/8" x 2 3/8" x 2 3/8"
RU 20A	1000	12'	12 vdc	4	1 1/8"	4" x 2 1/2" x 2 1/2"
RU 20F	800	12'	12 vdc	4	3/4"	4" x 2 1/2" x 2 1/2"
RU 25D	500	12'	12 vdc	2-1/2	3/4"	3 1/2" x 2 3/8" x 2 3/8"
RU 24	360	12'	12 vdc	2-1/2	3/4"	3 1/2" x 2 3/8" x 2 3/8"



JABSCO

450 - 3550 GPH PUMPS IN 12 & 24 VDC

Jabsco's traditional bilge pumps are activated by a panel or float switch purchased separately (see page 25 or 53). All models are totally submersible, ignition protected, and incorporate an anti-air lock feature.

Model Number	GPH at 1 foot	Max. Head	Volts	Amp Draw	Hose Dia.	Dimensions (H x W x L)
JA 30250-2012	3550	25'	12 vdc	16	1-1/2"	7 1/4" x 4 7/8" x 4 7/8"
JA 30250-2024	3550	25'	24 vdc	8	1-1/2"	7 1/4" x 4 7/8" x 4 7/8"
JA 30240-2024	1950	21'	24 vdc	5	1-1/8"	6" x 4 1/4" x 4 1/4"
JA 30240-2012	1950	21'	12 vdc	12	1-1/8"	6" x 4 1/4" x 4 1/4"
JA 30230-2012	1050	12'	12 vdc	4	1-1/8"	4" x 2 1/2" x 2 1/2"
JA 30230-2040	1050	12'	24 vdc	2	1-1/8"	4" x 2 1/2" x 2 1/2"
JA 30222-2012	750	12'	12 vdc	3	3/4"	3 1/2" x 2 3/8" x 2 3/8"
JA 30222-2024	750	12'	24 vdc	1.5	3/4"	3 1/2" x 2 3/8" x 2 3/8"
JA 30220-2012	450	12'	12 vdc	2	3/4"	3 1/2" x 2 3/8" x 2 3/8"



SHURFLO

1500 - 1800 GPH PUMPS IN 12 VDC

Shurflo's bilge pumps are commercial strength and built to last. They offer numerous hassle-free features such as a heavy-duty lubricated shaft seal to prevent damage during dry operation, a sleeved waterproof lead wire, ignition protection, and anti-air lock to clear trapped air.

Model Number	GPH at 0 foot	Volts	Amp Draw	Hose Dia.	Dimensions (H x W x L)
SF 1800-210-012	1800	12 vdc	9.5	1 1/8"	6 1/2" x 5" x 4"
SF 1500-110-012	1500	12 vdc	6	1 1/8"	6 1/2" x 5" x 4"



GROCO

1020 - 1560 GPH BRONZE PUMPS IN 12, 24, 32 VDC

Groco's totally submersible bilge pumps are built to last with a bronze housing, oversized motor, mechanical seal, and stainless steel inlet screen. They carry a 5 year warranty. A complete selection of service parts is available on page 138 if yours happens to fail after the warranty period.

Model Number	Volts	GPH at 0 feet	Max. Head	Amp Draw	Port Size	Dimensions (H x W x L)
GC BP-20-S	12 vdc	1020	11'	8	1/2" FPT / 3/4" GHT	8 1/2" x 3 1/2" x 3 1/2"
GC BP-20-S	24 vdc	1020	11'	5	1/2" FPT / 3/4" GHT	8 1/2" x 3 1/2" x 3 1/2"
GC BP-5009	12 vdc	1560	15'	20	3/4" FPT	9 1/2" x 4 3/4" x 4 3/4"
GC BP-5009	24 vdc	1560	15'	15	3/4" FPT	9 1/2" x 4 3/4" x 4 3/4"
GC BP-5009	32 vdc	1560	15'	10	3/4" FPT	9 1/2" x 4 3/4" x 4 3/4"

FOR ENGINEERING AND PUMP SELECTION ASSISTANCE CALL DEPCO AT 1-800-445-1656