

SELF-PRIMING



Engine Drive

SELF PRIMING CENTRIFUGALS IN GAS & DIESEL, UP TO 240 GPM

These engine powered self-priming centrifugal pumps are compact, lightweight and will lift up to 20 feet. Their pump heads are constructed of durable and corrosion resistant thermoplastic and are fitted with oil resistant Buna-N rubber gaskets and seals. These pumps utilize Briggs and Honda gasoline engines and Yanmar diesel engines. (See page 130 for service parts.)

Model Number	Port Size	HP	Engine Description Brand/Fuel	GPM at Feet of Head					Max. Head
				11	23	34	46	69	
DP 900G-GBY36B	2"	3.5	Briggs/Gasoline	147	141	129	100	60	102
DP 900G-GHY36B	2"	4	Honda/Gasoline	147	141	129	100	60	102
DP 900G-DYY36B	2"	4	Yanmar/Diesel	147	141	129	100	60	102
DP 910G-GBX36B	2"	5	Briggs/Gasoline	189	183	172	145	108	120
DP 910G-GHX36B	2"	5.5	Honda/Gasoline	189	183	172	145	108	120
DP 910G-DYG36B	2"	7	Yanmar/Diesel	189	183	172	145	108	120
DP 930G-GBX36B	3"	5	Briggs/Gasoline	240	240	188	120	40	87
DP 930G-GHX36B	3"	5.5	Honda/Gasoline	240	240	188	120	40	87
DP 940G-DYG36B	3"	7	Yanmar/Diesel	225	225	210	174	132	120

SELF-PRIMING



Electric Drive

SELF PRIMING CENTRIFUGALS IN 1 & 3 PHASE, UP TO 150 GPM

These electric powered self-priming centrifugal pumps are compact, lightweight and will lift up to 20 feet. Their pump heads are constructed of durable and corrosion resistant thermoplastic and are fitted with oil resistant Buna-N rubber gaskets and seals. These are available with single or three phase motors in a variety of enclosures including specs that meet IEEE-45, MCA, Lloyds, ABS and USCG requirements. (See page 130 for service parts.)

Model Number	Volts AC	Phase	HP	Motor Enclosure	Port Size	GPM at Feet of Head					Max. Head
						11	23	34	46	69	
DP 900C-10W36CT	115/230	1	2	TEFC	2"	130	125	107	66	15	65
DP 900C-30W36CT	230/460	3	2	TEFC	2"	130	125	107	66	15	65
DP 900D-10Y36C	230	1	3	ODP	2"	145	145	140	115	82	102
DP 900D-30Y36CT	230/460	3	3	TEFC	2"	145	145	140	115	82	102

SUBMERSIBLES



Bronze & Stainless

BRONZE & STAINLESS AC SUBMERSIBLES

These automatic submersible bilge pumps provide dependable high volume protection for unattended vessels. Powered by 115 vac shore power, they will not be affected by low battery or generator shutdown. The LG 8CBA and HY OSP-33A1BR2 have rugged bronze housings and a stationary diaphragm actuated switch that does not require any swing room. The EB 32Z707AU6.3S is stainless steel construction and comes with the standard swing float switch. (See other 115 vac submersible bilge pumps on page 23.)

Model Number	Pump Construction	Volts	Horse-Power	GPM at Foot of Head			Max Head	Discharge Port Size
				5	10	15		
LG 8CBA	Bronze	115 vac	4/10	3250	2500	1550	22.9'	1 1/2" FPT
HY OSP-33A1BR2	Bronze	115 vac	1/3	3500	3120	2520	24'	1 1/2" FPT
EB 32Z707AU6.3S	Stainless	115 vac	1/3	2375	2025	1560	26'	1 1/4" FPT

HOSE & FITTINGS



Also See Pages 52 & 53

COMPLETE HOSE KITS FOR SELF PRIMING & SUBMERSIBLES

These kits come complete with everything you need to operate your emergency pump. Two styles are available. The self-priming pump hose kit comes with 10 feet of non-collapsible suction hose and 25 feet of collapsible discharge hose. Both hoses have camlock fitting sets (including the pump half) on one end. The suction hose also has a strainer on its opposite end. The submersible kit comes with 25 feet of discharge hose with a camlock set (also including the pump half). Other combinations of hose sizes and fittings are available from our inventory upon your request.

Model	Size	Pump Type	Description of Items Contained in Kit
DP Hose Kit 1-1/2"	1-1/2"	Self-priming	10' suction, 25' discharge with fittings and strainer
DP Hose Kit 2"	2"	Self-priming	10' suction, 25' discharge with fittings and strainer
DP Hose Kit 3"	3"	Self-priming	10' suction, 25' discharge with fittings and strainer
DP Sump Hose 1-1/4"	1-1/4"	Submersible	25' discharge hose with fittings
DP Sump Hose 1-1/2"	1-1/2"	Submersible	25' discharge hose with fittings