

**REVERSIBLE OIL CHANGE / DIESEL TRANSFER**

These Jabsco pumps utilize the proven vane pump design, which is ideally suited for oil and diesel transfer. Each pump comes equipped with a three-way reversible switch that allows the removal of the old oil and the filling of the new. These pumps can be installed with a manifold (as shown on the bottom of the opposite page) to create a complete oil change system for your vessel. Each pump has 1/2" FPT internal ports with 1" external hose barbs and includes two adapters for 3/4" garden hose. The service kit includes the vanes, rotor, o-ring, and seal and can be ordered under the number JA 90200-0000. (Not for pumping gasoline!)

Model Number	Volts	Amp Draw	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 45710-1000	12 vdc	8	5	1/2" FPT & 3/4" GHT	3 3/8" x 4 3/4" x 8 5/8"

**OIL CHANGE / DIESEL TRANSFER PUMPS**

These Jabsco pumps are ideal for oil change or diesel transfer where a reversing switch is not required. Each pump has 1/2" FPT internal ports with 1" external hose barbs and includes 2 adapters for 3/4" garden hose. These service kit includes the vanes, rotor, o-ring, and seal and can be ordered under the number JA 90200-0000. (Not for pumping gasoline!)

Model Number	Volts	Amp Draw	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 45710-0000	12 vdc	8	5.5	1/2" FPT & 3/4" GHT	3 3/8" x 4 3/4" x 7 1/8"
JA 45710-0010	24 vdc	5	5.5	1/2" FPT & 3/4" GHT	3 3/8" x 4 3/4" x 7 1/8"

**115 VAC DIESEL TRANSFER PUMP**

The Jabsco 115 vac 45740-0000 pump will empty a 55 gallon drum of diesel in 7 minutes! It comes with a 6-foot power cord and has 1/2" FPT internal ports with 1" external hose barbs. The pump also includes two adapters for 3/4" garden hose. The service kit includes the vanes, rotor, o-ring, and seal and can be ordered under the number JA 90200-0000. (Not for pumping gasoline!)

Model Number	Volts	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 45740-0000	115 vac	8.5	1/2" FPT & 3/4" GHT	5 3/4" x 4 5/8" x 9 1/2"

**HIGH VOLUME DC DIESEL TRANSFER PUMPS**

These Jabsco high volume pumps are available in 12 and 24 vdc and 9, 12, and 25 gpm flows. The 50130 series has the added feature of an internal by-pass. This allows the fuel to be by-passed within the pump while the discharge line is restricted or shut-off during operation. This feature enables the user to start and stop the flow with a nozzle at the end of the hose, eliminating the need of controlling the flow with the power switch. (Not for pumping gasoline!)

Model Number	Volts	Amp Draw	Max GPM	Inlet/Outlet Ports	Dimensions (H x W x L)
JA 50130-1000	12 vdc	13	9	3/4" Barb	4" x 7" x 6 3/8"
JA 50130-1100	24 vdc	6	9	3/4" Barb	4" x 7" x 6 3/8"
JA VR050-1012	12 vdc	12	14	1" Barb	5 3/4" x 5" x 8 1/2"
JA VR050-1112	24 vdc	6	14	1" Barb	5 3/4" x 5" x 8 1/2"
JA VR100-1122	24 vdc	20	28	1 1/4" Barb	7 1/4" x 5 3/4" x 10 1/2"

