



Self-priming macerating or solids handling pumps are required to empty a holding tank. Small DC or AC powered models are available for on-board transfer as well as heavy-duty units that will easily empty the tank from dockside. Y-Valves (See page 48), allow the option of using either type. Toilets are available in manual or electric operation. Toilet conversion kits can be supplied to convert a manually operated pump to electric drive. (See page 46 and 47)

Galley Maid Pumps and Parts

Toilets and Water Systems

We maintain a complete inventory of replacement pumps and pump service parts for the Galley Maid toilets and water systems. A detailed listing of all the items we stock can be found on page 47. Don't forget... we also repair!

Progressing Cavity Macerator Pump

Robbins & Myers

This rugged design will easily pass the most challenging solids. It utilizes a hardened stainless screw shaped rotor that spins inside a rubber stator to move up to 15 GPM. It is available in AC and DC voltages as well as custom configurations. (See page 64)

25 GPM Macerator in DC and AC Voltages

Oberdorfer 406M Series

Oberdorfer's 1 HP, bronze macerator pump develops tremendous suction to empty your boat's holding tank from onboard or dockside. It will move up to 25 GPM and is available in DC or AC voltages as well as custom configurations. (See page 43 and 64)

Designer Toilets in White and Bone

Jabsco's DS14 & DS17

Jabsco's elegant designer toilets have sleek contours and are available in white or bone china finish. They can be connected to your current water system supply or can be supplied with their own salt or fresh water supply pump. (See page 44)

Sealand Pumps for Toilets and Discharge

Vacuflush System

Depco inventories Sealand's "S" series vacuum pumps utilized on their "Vacuflush" toilet systems as well as their durable "T" series discharge pump. Both pumps will run dry without damage. A complete selection of service parts is also available. (See page 43)

High Capacity Sewage Transfer - to 480 GPM!

2", 3" and 4" Ports

AMT's self-priming sewage pump is available in sizes from 3 to 15 HP and flows from 60 to 480 GPM. They have a cast iron housing, silicon carbide seal, stainless steel clog resistant impeller, and built-in check valve. (See page 64)

Dry Run Macerator!

Jabsco's 18590-1000

Jabsco has incorporated an exclusive (patent pending) run-dry protection device that makes accidental run-dry impeller damage a thing of the past! They are available in 12 and 24 VDC. (See page 42)

20 GPM Diaphragm Pump for Sewage

Bronze or Aluminum

This 2" self-priming diaphragm pump will empty your boat's holding tank from onboard or dockside. It will easily pass solid without clogging or damage and is available in DC or AC voltages as well as custom configurations. (See page 64)