

1HP, 25 GPM DOCKSIDE OR ON-BOARD MACERATOR PUMP

Oberdorfer's 406M is the largest series marine macerator pump available and comes in single and three phase, 12 and 24 vdc, 50 and 60 hz, and in custom configurations including models that meet IEEE-45, MCA, Lloyds, ABS and USCG specifications. The optional 406MK series comes equipped with a vacuum switch which shuts down the pump once the holding tank is empty. The suction port is 1 1/2" MPT or 2" slip-on and the discharge port is 1" FPT or 1 1/2" slip-on. Service kit = OB 10956. (See page 123 for service parts.)

Model Number	Volts	HP	Max. GPM	Inlet Port	Outlet Port
OB 406M-4-N26	115/230 vac	1	25	1 1/2" MPT & 2" Slip-on	1" FPT & 1 1/2" Slip-on
OB 406MK-4-N26	115/230 vac	1	25	1 1/2" MPT & 2" Slip-on	1" FPT & 1 1/2" Slip-on
OB 406M-4-30N18BCT	115/230 vac	1	25	1 1/2" MPT & 2" Slip-on	1" FPT & 1 1/2" Slip-on
OB 406M-4-12N18BCT	12 vdc	1	25	1 1/2" MPT & 2" Slip-on	1" FPT & 1 1/2" Slip-on
OB 406M-4-24N18BCT	24 vdc	1	25	1 1/2" MPT & 2" Slip-on	1" FPT & 1 1/2" Slip-on



OBERDORFER

3/4 HP, 18 GPM DOCKSIDE PUMP WITH HOSE & DECK ADAPTOR

The Jabsco 6050-0713 is a complete dockside pump-out system including 15 feet of suction hose, right angle deck fitting nozzle, automatic shut off vacuum switch, and wire/plug assembly. The discharge port can be fitted with 1" FPT nipple for 1 1/4" or 1 1/2" hose (not included) and can pump a distance of up to 25 feet. Service kit = JA 90058-0003. (See page 122 for service parts.)

Model Number	Volts	HP	Max. GPM	Inlet Fitting	Outlet Port
JA 6050-0713	115 vac	3/4	18	1 1/2" Tapered Deck Fitting	1" FPT



JABSCO

DRY RUNNING DIAPHRAGM WASTE PUMP

Straight through flow passes solids easily (it handles both macerated and non-macerated waste)... can run dry without pump damage! This ultra compact pump is very quiet running. While pumping fluid, it has a continuous duty rating of up to one-half hour. All mechanical moving parts are fully shrouded for maximum safety. Self-priming to six feet. Pumps up to six gallons per minute. Has 1 1/2" hose barbed port connections. Service kit = JA 90220-0000.

Model Number	Volts	Max. GPM	Inlet / Outlet	Dimensions (H x W x L)
JA 59090-0012	12 vdc	6	1 1/2" Barb	7 3/4" x 11" x 11"
JA 59090-0024	24 vdc	6	1 1/2" Barb	7 3/4" x 11" x 11"



JABSCO

SEALAND MACERATOR & VACUFLUSH PUMPS

Sealand originally developed the rugged "T" series line of bellows sewage discharge pumps for their own toilet systems. However, it was so successful they have made it available for all sewage discharge applications. These pumps will move up to 200 GPH, handle 1/2" diameter solids, and accept 1 1/2" slip-on hose (1 1/2" x 1" hose adaptor is included). The "S" series vacuum pump are specifically for use on Sealand's "Vacuflush" toilet systems. They are designed for single toilet installations, draw 6 amps and can run dry.

Model Number	Volts	Type	Valve Kit	Bellows	Motor
SL T12	12 vdc	Discharge Pump	SL 310076	SL 230980	SL 310245
SL T24	24 vdc	Discharge Pump	SL 310076	SL 230980	SL 310246
SL T32	32 vdc	Discharge Pump	SL 310076	SL 230980	SL 310247
SL S12	12 vdc	Vacuum Pump	SL 310076(2)	SL 230980	SL 310245
SL S24	24 vdc	Vacuum Pump	SL 310076(2)	SL 230980	SL 310246
SL S32	32 vdc	Vacuum Pump	SL 310076(2)	SL 230980	SL 310247



SEALAND