

UP TO 100 GPM, 1-3 HP, IN BRONZE & C.I.

The Burks WA6 series is a high volume water system pump capable of delivering up to 100 gpm. Sizes range from 1 to 3 horsepower and are available in bronze or cast iron construction, single or three phase, 50 or 60 hz, IEEE-45 enclosure and custom configurations that meet MCA, Lloyds, ABS and USCG specifications. Below are some examples of the sizes available. Call us for information on the configuration to meet your requirements.

Bronze Model 115/230 vac 60 hz	Bronze Model 230/460 vac 60 hz	HP	GPM at PSI		Inlet/Outlet
			20	40	
BU WA6B-10N36J	BU WA6B-30N36J	1	52	23	1-1/2" x 1-1/2"
BU WA6B-10T36J	BU WA6B-30T36J	1-1/2	61	24	1-1/2" x 1-1/2"
BU WA6B-10W36J	BU WA6B-30W36J	2	73	37	1-1/2" x 1-1/2"
BU WA6B-10Y36J*	BU WA6B-30Y36J	3	93	50	1-1/2" x 1-1/2"

*230v only



UP TO 32 GPM, 150 PSI, IN BRONZE & C.I.

The Burks CS series turbine pump design delivers high pressure to all areas of your vessel. Sizes range from 1 to 5 horsepower and are available in bronze or cast iron construction, single or three phase, 50 or 60 hz, IEEE-45 enclosure and custom configurations that meet MCA, Lloyds, ABS and USCG specifications. Below are some examples of the sizes available. Call us for information on the configuration to meet your requirements.

115/230 vac Bronze Number	Hz	230/460 vac Bronze Model	Hz	HP	GPM at PSI				Max PSI	Inlet/Outlet
					20	50	100	150		
BU 10CS5MB	60	BU 310CS5MB	50/60*	1	10	9	-	-	97	1-1/4" x 1"
BU 15CS6MB	60	BU 315CS6MB	50/60*	1-1/2	15	13	10	-	108	1-1/4" x 1"
BU 20CS6MB	60	BU 320CS6MB	50/60*	2	15	13	10	9	131	1-1/4" x 1"
BU 20CS7MB	60	BU 320CS7MB	50/60*	2	19	16	-	-	86	1-1/4" x 1"
		BU 330CS8MB	60	3	25	22	-	-	97	1-1/4" x 1"
		BU 350CS9MB	60	5	31	28	23	20	151	1-1/4" x 1"

*Flows shown are at 60 Hz.



UP TO 20 GPM, 1/2 - 1 HP IN STAINLESS STEEL

These stainless steel centrifugal water system pumps provide up to 20.5 gpm and up to 50 psi. They are available in single and three phase, 50 and 60 hz, IEEE-45 enclosure and custom configurations to meet MCA, Lloyds, ABS and USCG specifications. Below are some examples of the sizes available. Call us for information on the configuration to meet your requirements.

Model Number	Voltage	Hz	Phase	HP	GPM @ 20 PSI	Inlet/Outlet
GF JP-5 SW	115/230 vac	60	1	1/2	13.3	1-1/4" x 1"
GF JP-5-30J36BJ	230/460 vac	60	3	1/2	13.3	1-1/4" x 1"
GF JP-7 SW	115/230 vac	60	1	3/4	17.1	1-1/4" x 1"
GF JP-7-30M36BJ	230/460 vac	60	3	3/4	17.1	1-1/4" x 1"
GF JP-10 SW	115/230 vac	60	1	1	20.5	1-1/4" x 1"
GF JP-10-30N36BJ	230/460 vac	60	3	1	20.5	1-1/4" x 1"



UP TO 55 GPM, 116 PSI IN STAINLESS STEEL

The Grundfos CHI series provide a high quality stainless AC water supply for single and three phase systems. A variety of models are available to deliver your required flow and pressure requirements. Pumps do not come with a demand pressure switch (supplied separately).

Model Number	Voltage Options	HP Range	Flow Range	Pressure Range	Ports
CH 2 Series	115/230/460	1/3 - 1	1.2 - 20 gpm	7 - 116 psi	1"
CH 4 Series	115/230/460	1/3 - 1	3 - 40 gpm	7 - 100 psi	1 1/4"
CH 8 Series	115/230/460	1/3 - 1	4 - 55 gpm	11 - 75 psi	1 1/2"

