

**LITTLE GIANT**



**LITTLE GIANT PUMPS FOR MARINE AIR P510 & P310**

Marine Air #P510 (3MD-SC / 500 GPH up to 24,000 BTU)  
Marine Air #P310 (5MD-SC / 1000 GPH up to 48,000 BTU)

Model Number	Volts	HP	Cycle	GPH at Feet of Head			Max. Head	Ports	
				1'	3'	6'		Inlet	Outlet
LG 3MD-SC 115V	115 vac	1/12	60	750	710	665	22	3/4" FPT	1/2" MPT
LG 3MD-SC 230V	230 vac	1/12	60	750	710	665	22	3/4" FPT	1/2" MPT
LG 5MD-SC 115V	115 vac	1/8	60	1050	990	920	27	1" FPT	1/2" MPT
LG 5MD-SC 230V	230 vac	1/8	50/60	1050	990	920	27	1" FPT	1/2" MPT

**CAL**



**CAL MARINE FOR MARINE AIR, CRUISAIR & MORE!**

Marine Air #PC400 = CA MS 320B / #PC500 = CA MS 580B  
Cruisair #PDS400 = CA MS 320B / #PDS500 = CA MS 580B / #PDS900 = CA MS 900B  
Mermaid = CA MS 430B

Model Number	HP	GPH at Feet of Head					Max. Head	Ports	
		1'	3'	5'	9'	13'		Inlet	Outlet
CA MS2700(B)	1/4	2690	2550	2410	2090	1690	23	1" FPT	1" MPT
CA MS1200(B)	1/9	1200	980	840	660	540	20	3/4" MPT	1/2" MPT
CA MS900(B)	1/12	900	720	620	425	390	17	3/4" MPT	1/2" MPT
CA MS580(B)	1/15	580	425	390	320	260	15	3/4" MPT	1/2" MPT
CA MS430(B)	1/40	430	370	300	250	200	16	1/2" MPT	3/8" MPT
CA MS320(B)	1/40	320	260	200	140	—	12	1/2" MPT	1/4" MPT

**SHURFLO**



**SHURFLO IGNITION PROTECTED MAGNETIC DRIVE**

The Shurflo 1600 series utilizes a state-of-the-art electronic drive that has no moving parts except the impeller! It is submersible to 5 feet and has run dry, thermal overload, and ignition protection. Must be mounted below the waterline with a flooded suction.

Model Number	Volts	Amps	GPH at Feet of Head			Max. Head	Ports	
			1'	3'	5'		Inlet	Outlet
SF 1600-201-00	115 vac	1.5	570	522	492	17.5	3/4" MPT	1/2" MPT

**MARCH & PROVEN**



**KING AIR & MERMAID REPLACEMENT PUMPS**

The most common King Air coolant pump is the March magnetic drive model MDX-3 5/8". This pump has an open motor and requires flooded suction. Mermaid often utilizes the Proven oil-filled centrifugal model B500. Its unique shape and bright red motor housing makes it easy to recognize. Both of these pumps can be upgraded to longer life models. Call us for details.

Model Number	Volts	Watts	Amps	GPH at Feet of Head			Max. Head	Ports	
				1'	3'	6'		Inlet	Outlet
MA MDX-3 5/8	115 vac	108	1.35	510	480	420	19	5/8" OD	5/8" OD
PR B500	115 vac	75	1.50	500	360	300	11	3/4" GHT	3/8" MPT

**SCOT**



**SCOT PUMP FOR MARINE AIR P100**

Scot manufactures a dual voltage (115/230 vac) and dual cycle (50/60hz) pump specifically to meet Marine Air's rigorous requirements. Service parts are also available.

Model Number	Volts	HP	Cycle	GPH at Feet of Head			Max. Head	Ports	
				1'	3'	6'		Inlet	Outlet
SC 68	115 / 230 vac	1/3	50/60	1800	1770	1740	35	1-1/4" FPT	1" FPT

\* For below waterline installations