

# JABSCO IMPELLER IDENTIFICATION GUIDE

CONTENTS

ENGINE COOLING

INDEX

HOME

NEXT

BACK

IMPELLER NUMBER	DRIVE MATERIAL	TYPE	NO. OF BLADES	DIAMETER		WIDTH		SHAFT DIA.		INSERT MATERIAL	REMARKS
				INCH	MM	INCH	MM	INCH	MM		
<b>SILHOUETTE L</b>											
3085-0001	Neoprene	7	10	2 1/4	57	1 1/4	31.5	5/8	16	BR	
18815-0005	Neoprene	6	10	2 1/4	57	1 1/4	31.5	5/8	12.7	BR	SS Extended Drive Cup (Sanitary)
<b>SILHOUETTE M</b>											
920-0001	Neoprene	7	8	2 9/16	65	2	51	5/8	16	BR	
-0003	Nitrile	7	8	2 9/16	65	2	51	5/8	16	BR	
-0008†	Natl. Rub.	7	8	2 9/16	65	2	51	5/8	16	BR†	For Low Temp. to 27°F - Max. 120°F
4598-0001	Neoprene	3	8	2 9/16	65	2	51	5/8	16	BR	Was D-12
-0003	Nitrile	3	8	2 9/16	65	2	51	5/8	16	BR	Was D-12-37
6056-0003	Nitrile	6	8	2 9/16	65	2	51	5/8	16	BR	SS Extended Drive Cup
11979-0001	Neoprene	7	8	2 9/16	65	1 7/16	36.5	5/8	16	BR	
17018-0001	Neoprene	7	8	2 9/16	65	3	76.2	5/8	16	BR	
<b>SILHOUETTE O</b>											
836-0001	Neoprene	7	9	3 3/4	95	2 1/2	63	1	25	BR	
-0003	Nitrile	7	9	3 3/4	95	2 1/2	63	1	25	BR	
-0008†	Natl. Rub.	7	9	3 3/4	95	2 1/2	63	1	25	BR†	
6760-0001	Neoprene	7	9	3 3/4	95	3 1/2	88.9	1	25	BR	
-0003	Nitrile	7	9	3 3/4	95	3 1/2	88.9	1	25	BR	
-0008	Natl. Rub.	7	9	3 3/4	95	3 1/2	88.9	1	25	BR†	
<b>SILHOUETTE Q</b>											
17370-0001	Neoprene	5	12	3 3/4	95	3 1/2	88.9	1	25	PL	
17935-0001	Neoprene	7	12	3 3/4	95	2 1/2	63	1	25	BR	Alternative to 836-0001
17936-0001*	Neoprene	7	12	3 3/4	95	3 1/2	88.9	1	25	BR	Alternative to 6760-0001
21676-0003	Neoprene	7	12	3 3/4	95	3 1/2	88.9	1	25	BR	U.K. Equivalent to 17936-0001
<b>SILHOUETTE R</b>											
17240-0001	Neoprene	7	9	4 5/8	118	3 1/2	88.9	1	25	BR	
18786-0001	Neoprene	5	9	4 5/8	118	3 1/2	88.9	1	25	PL	
18789-0001	Neoprene	7	9	4 5/8	118	3 1/2	88.9	1	25	BR	Replaces UK 17240-0001
<b>SILHOUETTE U</b>											
2999-0001	Neoprene	7		13	5	127	4	101.6	1 1/2	38	BR
<b>SILHOUETTE W</b>											
18838-0001	Neoprene	3	12	2 7/16	62	1 1/4	31.5	5/8	16	BR	Replaces Sherwood 9959 Impeller
<b>SILHOUETTE X</b>											
18948-0001	Neoprene	3	12	2 9/16	65	1 5/8	41.4	5/8	16	BR	Replaces Sherwood 10615 Impeller
<b>SILHOUETTE Y</b>											
17937-0001	Neoprene	7	10	2 9/16	65	2	51	5/8	15	BR	Replaces 920-0001
-0003	Nitrile	7	10	2 9/16	65	2	51	5/8	16	BR	
17954-0001	Neoprene	4	10	2 9/16	65	2	51	3/4	19	BR	MerCruiser Replacement
17956-0001	Neoprene	6	10	2 9/16	65	2	51	5/8	16	BR	SS Drive Cup, Replaces 6056-0001
18327-0001	Neoprene	3	10	2 9/16	65	2	51	5/8	16	BR	Replaces Sherwood 15000 Impeller
<b>SILHOUETTE Z</b>											
30919-0001	Neoprene	5	12	3 1/16	77	3	76.2		20	BR	
<b>SILHOUETTE CC</b>											
31130-0061	Neoprene	7	10	2 19/32	50.8	2 11/16	68.2	5/8	15	R	MerCruiser Replacement (HINO) (Replaces Quicksilver 47-831311350)
<b>SILHOUETTE GG</b>											
18958-0001	Neoprene	3	12	3 1/4	95	2 57/64	73.4	25/32	20	BR	Replaces Sherwood 17000 Impeller

INSERT MATERIAL: BR = Bronze, SS = Stainless Steel and PL = Plastic

† = For Low Temp. to 27°F Max. 120°F

\* = The 17936-0001 impeller may be used to replace an English Model 21676-0001.