

# SHURFLO AND GALLEY MAID WATER SYSTEMS

CONTENTS

## 1 TO 4 GPM, "AQUA KING" WATER SYSTEMS

The new "Aqua King" diaphragm pumps from Shurflo replace the popular 2088 series. Designed and built specifically for the harsh marine environment, these next generation pumps include sealed switches and seamless e-coated motors. See page 64 for other port fitting options and page 158 for service parts.

ENGINE COOLING

INDEX

HOME

NEXT

BACK

Model	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 1901-0013	1.0	12vdc	3 amps	30	1/2" Barb & 1/2" Qest MPT	3.2" x 4.5" x 6.4"
SF 2901-0213	2.0	12vdc	4 amps	30	1/2" Barb & 1/2" Qest MPT	5.0" x 4.6" x 7.3"
SF 3901-0216	3.0	12vdc	6 amps	55	1/2" Barb & 1/2" Qest MPT	5.0" x 4.6" x 7.3"
SF 3901-1216	3.0	24vdc	3 amps	55	1/2" Barb & 1/2" Qest MPT	5.0" x 4.6" x 7.3"
SF 4901-4212	4.0	12vdc	10 amps	45	1/2" Barb & 1/2" Qest MPT	5.4" x 5.3" x 7.2"

## SHURFLO




Aqua King

## 4 AND 5.5 GPM, "EXTREME" SERIES WATER SYSTEMS WITH ACCUMULATOR

The Extreme series pumps with accumulator from Shurflo are fully automatic and come complete with suction strainer and NSF certified stainless steel 2 gallon accumulator tank. The 4902 series supplies up to 4 gpm and comes equipped with a 45 psi pressure switch. The 5902 series supplies up to 5.5 gpm and also comes equipped with a 45 psi pressure switch. See page 158 for service parts on both sizes.

Model	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 4902-2212	4.0	12 vdc	10 amps	45	3/4" Barb or 1 1/2" Qest MPT	14.5" x 13" x 14"
SF 5902-2212	5.5	12 vdc	12.4 amps	45	3/4" Barb or 1 1/2" Qest MPT	14.5" x 13" x 14"
SF 5902-3212	6.5	24 vdc	6 amps	45	3/4" Barb or 1 1/2" Qest MPT	14.5" x 13" x 14"

## SHURFLO




Accumulator System

## 10 GPM EXTREME PRO-BLASTER AND SMART SENSOR COMBO

The Smart Sensor is designed specifically for midsize and large yachts. Delivering 10 gpm and pressure up to 60 psi, this micro-controller based variable speed and Extreme Pro-Blaster combination pumps precisely, monitors the system's water flow demand and adjusts the motor speed of the Smart Sensor maintaining the Extreme Pro-Blaster pump on stand by, eliminating the need for an accumulator tank.

Model	Max GPM	Volts	Max. Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 5907-5304	10	12 vdc	12/14	60	3/4" Barb	6.8" x 10.4" x 19.4"
SF 5907-6304	10	24 vdc	5/6	60	3/4" Barb	6.8" x 10.4" x 19.4"

## SHURFLO



Sensor Combo

## 7-10 GPM GALLEY MAID MR-SERIES

The Galley Maid Water Pressure System pump model MR-Series is available as new or rebuilt pumps. Depco also stocks repair parts.

Model	Max GPM	Voltage	Breaker Size	Inlet & Outlet	Dimensions (H x W x L)
MR-12-7	7	12 vdc	40 amps	3/4" NPT / 1/2" NPT	12 1/2" x 10" x 21"
MR-24-7	7	24 vdc	30 amps	3/4" NPT / 1/2" NPT	12 1/2" x 10" x 21"
MR-32-7	7	32 vdc	25 amps	3/4" NPT / 1/2" NPT	12 1/2" x 10" x 21"
MR-AC-7	7	115 vac	15 amps	3/4" NPT / 1/2" NPT	12 1/2" x 10" x 21"
MR-12-10	10	12 vdc	40 amps	1" NPT / 3/4" NPT	14 1/2" x 10" x 21"
MR-24-10	10	24 vdc	30 amps	1" NPT / 3/4" NPT	14 1/2" x 10" x 21"
MR-32-10	10	32 vdc	25 amps	1" NPT / 3/4" NPT	14 1/2" x 10" x 21"
MR-AC-10	10	115 vac	15 amps	1" NPT / 3/4" NPT	14 1/2" x 10" x 21"

\* Pump models available as new or rebuilt

## GALLEY MAID



MR-Series