

Announcing Powerful New Drum Pump Motors

800 WATT - UNIVERSAL, VARIABLE SPEED



800W Motor Advantages:

- Precise adjustment of fluid flow with speed regulator
- Expands PF Series fluid viscosity range from 500 to 2000 cP
- Achieves higher flow rates for high SG fluids (such as concentrated sulfuric acid) with PF Series
- TEFC/IP54 enclosure protects motor internals from corrosive attack and damage from damp or dirty environments

Available with HVDP and PF Series drum/barrel pumps.

All have 12 ft. (3.5 m) cord, circuit breaker with manual reset, and built in on-off switch. All are continuous duty rated.

Model	Part Number	Electrical Requirements	Enclosure	Type	HP	Speed RPM	Certification	Tube Series Fit
M58H	105072	115VAC/50-60Hz	TEFC	variable speed	1	10,000	NRTL	HVDP
M59H	105073	230VAC/50-60Hz	TEFC/IP54	variable speed	1	10,000	CE	HVDP
M58P	105074	115VAC/50-60Hz	TEFC	variable speed	1	10,000	NRTL	PF
M59P	105075	230VAC/50-60Hz	TEFC/IP54	variable speed	1	10,000	CE	PF



FINISH THOMPSON INC.

921 Greengarden Road • Erie, PA 16501-1591 U.S.A.
Ph 814-455-4478 • Fax 814-455-8518
Email fti@finishthompson.com • www.finishthompson.com