

DRUM Pumps

CONTAINER

EMPTYING

SOLUTIONS



FINISH THOMPSON INC.

**Portability
and Safety —
A few of many
FTI advantages**

Container emptying is accomplished quickly, efficiently and safely with Finish Thompson powered, portable drum pumps. Utilizing FTI drum pumps, containers are filled or emptied without messy spills and splashes. Operator contact or exposure to potentially harmful materials is avoided. All FTI pumps are designed with the user in mind. Compact, impact-resistant motor housings have integral, comfort-grip handles with easy access to on/off switches. Interchangeable tubes and motors are easy to clean and maintain.

FTI has been a leading designer and manufacturer of drum pumps since 1972. Strict process controls and an ISO 9001 Quality System assure consistency of product quality. Inventoried and sold through worldwide distribution, FTI drum pumps are available for immediate delivery and carry CSA or European certifications.

A "quick-response" team, staffed by experienced product technicians, provide application and pump selection assistance. FTI's Technical Service Department offers post installation support and dedicated access via a toll free service number.

A typical pump user will find the FTI drum pump a viable replacement for pouring, hand pumps or diaphragm pumps. Drum pumps are easier to use, more mobile and less costly to operate.

**Try our handy on-line pump selector
at www.finishthompson.com!**



Before



After



EP Series

BEST VALUE
LIGHT DUTY



Features

- Handles mild corrosives, acids and chemicals
- Up to 1.2 SG
- Portable and light weight (5lbs./2.3 kg.)
- Polypropylene tube - 316SS or Alloy 625 shaft
- 27" (69 cm) and 40" (102 cm)
- Intermittent duty motors: 50/60 Hz; 110, 120 or 220/240 VAC
- **SP**, **CE**, ATEX 100 or NRTL certifications
- Push-button operation
- Splashproof motor



AIR MOTOR



ELECTRIC MOTORS



EPP

NOTE: The Econo Pump (EP) is not for use with flammables or pumping in hazardous locations.



PF Series

MOST VERSATILE
HIGH FLOW

Features

- Sealless
- Handles acids, caustics, chemicals and flammables
- Up to 1.8 SG
- Tubes and motors interchangeable
- Polypropylene, PVDF and 316SS
- 27" (69 cm), 40" (102 cm), 48" (122 cm), 60" (152.4 cm), 72" (182.9 cm)
- Continuous duty motors: 50-60 Hz; 115 or 230 VAC, variable speed
- **SP**, **CE** and NRTL certifications
- Impact resistant housing with integral handle



AIR MOTORS
(shown with regulator
valve and muffler)

M6



ELECTRIC MOTORS



PFV

PFP



PFS



TB Series

LIGHT-MEDIUM
VISCOSITY
MEDIUM FLOW

Features

- Sealed
- Mild corrosives and solvents
- Up to 1.4 SG
- 316SS construction
- 40" (102 cm)
- Continuous duty motors: 50-60 Hz; 115 or 230 VAC
-  or  certifications
- Impact resistant housing with integral handle



AIR MOTORS
(shown with regulator
valve and muffler)



ELECTRIC MOTORS





TBS



TBP Series

LIGHT-MEDIUM
VISCOSITY
MEDIUM FLOW

Features

- Sealed
- Handles corrosive liquids
- Up to 1.4 SG
- Pure polypropylene/pure PTFE construction
- 27" (69 cm), 40" (102 cm), 48" (122 cm)
- Continuous duty motors: 50-60 Hz; 115 or 230 VAC
-  or  certifications
- Impact resistant housing with integral handle

*Recommended
for
bleach applications*



AIR MOTOR
(shown with regulator
valve and muffler)



ELECTRIC MOTORS



TBP



BT Series

HIGH VISCOSITY
HIGH HEAD

Features

- Sealed
- Mild corrosives, flammables, explosionproof locations
- Up to 1.8 SG, 15,000 cP
- 316SS construction
- 40" (102 cm) tube
- Continuous duty motors: 50-60 Hz; 115 or 220-230 VAC
UL or SP certifications
- Rugged construction

M15 and M19 are typical representations.

Other models not shown:

M16, M17, M18, M20
M27, M28, M29, M39, M40,

Explosionproof: M45X, M46X, M47X



Air motor (M19) shown
with regulator
valve and muffer



M15



BTS



TT Series

MEDIUM VISCOSITY
MEDIUM FLOW

Features

- Sealed
- Corrosives, flammables, sanitary and pure applications
- Up to 1.8 SG
- Tubes and motors interchangeable
- CPVC, 316SS or USDA sanitary stainless
- 27" (69 cm), 40" (102 cm), 48" (122 cm)
- Continuous duty motors: 50-60 Hz; 115 or 220 VAC
SP or CE certifications
- Impact resistant housing with integral handle



M6X

AIR MOTORS
(shown with regulator
valve and muffer)



M6



M7T

M7X

M8T

ELECTRIC MOTORS



TTS



TTC



STS



HVDP Series

HIGH VISCOSITY
HIGH HEAD

Features

- Sealed, progressive cavity design
- Handles viscous chemicals, cosmetics, food and beverage products
- Up to 100,000+ cP, 300 feet (91 m) head
- Exclusive camlock feature allows easy disassembly for cleaning
- 316SS construction
- 27" (69 cm), 40" (102 cm) tube, 48" (122 cm)
- Gear reducer design enables use of universal, induction or air motors
- CE, UL, and NRTL motor certifications
- Impact resistant housing with integral handle



M65/M66

AIR MOTOR
(shown with regulator
valve and muffler)



M58H/M59H



M60, M61, M62,
M63, M64

ELECTRIC MOTORS



HVDP



TM Series

MEDIUM VISCOSITY
DRUM MIXER

Features

- Sealed
- Mild corrosives, solvents or flammables
- Non-aerating, non-vortexing circulation
- 316SS construction
- 40" (102 cm)
- Continuous duty motors: 50-60 Hz; 110 or 220 VAC
- SF or CE certifications
- Impact resistant housing with integral handle



M6X

AIR MOTOR
(shown with regulator
valve and muffler)



M7T

M7X

M8T

ELECTRIC MOTORS



TMS

TUBES

- P= Polypropylene
- S= 316SS
- V = PVDF
- C= CPVC
- PP= Pure Polypropylene/
Pure PVDF

TUBE APPLICATIONS	MAX. FLOW Air/Electric		MAX. HEAD Air/Electric		MAX. VISCOSITY Air/Electric		MATERIAL	PUMP MODELS	APPLICABLE MOTORS
	GPM	LPM	Feet	Meters	cP				
	6	22	12	3.7	150		P	EPP-S, EPP-I	M54, M55, M56, M57
	15/20	57/76	16/28	5/9	200		s	TBS	M3, M3T, M5, M5T M6, M6X, M10X
	16/10	60/38	30/10	10/3	2,000/400		C, S & Sanitary S	TTC, TTS, STTS	M6, M7T, M8T, M6X, M7X
	10	38	200	61	15,000		S	BTS	M15, M16, M17, M18, M19, M20, M24X, M25X, M26X, M27, M28, M29, M39, M40
	30/40	113/150	60/80	18/24	330/2000		P, V, S	PFP, PFS, PFV	M3, M3T, M3X, M5, M5T, M5X, M6, M6X, M10X, M58P, M59P
	12.5/20	47.3/75.7	19/39.5	5.8/12	200		PP	TBP	M3, M3T, M5, M5T, M6, M10X
	8.5	32	300	91	100,000*		S	HVDP	M58H, M59H, M60, M61, M62, M63, M64, M65, M66

Mild Corrosives, Acids, Chemicals
Light Viscosity/Low Flow

Mild Corrosives, Acids, Chemicals
Light to Medium Viscosity/Low to Medium Flow

Mild Corrosives, Acids, Chemicals
Light to Medium Viscosity/High Flow

Corrosives, Acids, Chemicals
Light to Medium Viscosity/Medium to High Flow

Strong Corrosives, Acids, Chemicals
Light to Medium Viscosity/Medium to High Flow

Mild corrosives and chemicals
High Viscosity, High Head

Solvents, Flammables, Hazardous Locations
Light, Medium or High Viscosity

MOTORS

MOTOR MODELS	CSA	CE	WEATHERPROOF		TEFC		EXPLOSION PROOF		AIR
			115V/50-60Hz	230V/50-60Hz	115V/50-60Hz	230V/50-60Hz	115V/50-60Hz	230V/50-60Hz	
			100-373W	100W	186-2237W	180-2237W	75-186W	746-2237W	
M54									
M55									
M56									
M57									
M3									
M3T									
M3X									
M5									
M5T									
M5X									
M7T									
M7X									
M8T									
M6									
M6X									
M10X									
M15									
M16									
M17									
M18									
M19									
M20									
M24X									
M58H/P	NRTL								
M59H/P									
M60									
M65									

SPLASHPROOF IP24 OR IP44

DUSTPROOF IP54

FLAMEPROOF IP54

NOTE: Additional motor options are available for BTS and HVDP pump models.

Pumping Solutions

WORLDWIDE



FINISH THOMPSON INC.

921 Greengarden Road • Erie, PA 16501-1591 U.S.A.
Ph 814-455-4478 • Fax 814-455-8518

Email fti@finishthompson.com • www.finishthompson.com

Toll Free USA & CANADA 1-800-934-9384
Literature ID Number FT99-7351, 8-4-05