Depco Home

FINISH THOMPSON INC.

DRUM PUMPS ACCESSORIES

Flow Meters

U.S. GALLONS

PART NO.	DESCRIPTION
A101523	ALUMINUM FLOW METER - 3 TO 50 GPM, MAX PSI 300
A101524	NYLON FLOW METER - 3 TO 50 GPM, MAX PSI 150
A101525	316SS FLOW METER - 3 TO 50 GPM, MAX PSI 800

METRIC

PART NO.	DESCRIPTION
A101527	1" ALUMINUM FLOW METER - 10 TO 190 LPM, MAX BAR 20.7
A101528	1" NYLON FLOW METER - 10 TO 190 LPM, MAX BAR 10.3
A101529	1" 316SS FLOW METER - 10 TO 190 LPM, MAX BAR 55.2

- QUALITY BUILT
- FIELD REPLACEABLE LITHIUM BATTERIES
- ENCAPSULATED ELECTRONICS FOR MOISTURE PROTECTION
- THE TOTALIZS - 1 CUMULATIVE AND 2 RESETTABLE
- THREE CALIBRATION CURVES WITH UP TO 5 CALIBRATION POINTS
- RATE OF FLOW WITH BYPASS
- ONE YEAR FACTORY WARRANTY
- MODELS ALSO COME WITH A 1" CLOSE NIPPLE

Nozzles



PART NO.	DESCRIPTION
A101497	1" POLYPROPYLENE DISPENSING NOZZLE • FLOW RATE TO 27 GPM • MAX 75 PSI • STAINLESS HANDLE, SPRING AND PIN • TEFLON BUSHING • VITON RUBBER PARTS • QUICK RELEASE ACTION • INCLUDES POLYPRO HOSE BARB AND SS CLAMP THIS PRODUCT HAS A WIDE RANGE OF INDUSTRIAL AND AGRICULTURAL APPLICATIONS. IT IS IDEAL FOR FILLING CONTAINERS WITH MILD CORROSIVE FLUIDS.
A101522	1" SINGLE UNION POLY VALVE WITH ANGLE HOSE END • FLOW RATE TO 40 GPM • NO FLUID CONTACT WITH METAL PARTS • INCLUDES POLYPRO HOSE BARB AND SS CLAMP THIS VALVE IS IDEAL FOR MORE PRECISE METERED FILLING OPERATIONS. USE WITH CORROSIVE MATERIALS.
J101929	1" ALUMINUM DISPENSING NOZZLE • FLOW RATE 17 GPM AT 34 PSI • QUICK RELEASE ACTION • USE FOR DISPENSING FLAMMABLES USE THIS VALVE WHEN DISPENSING FLAMMABLE LIQUIDS. WHEN THE NOZZLE IS PART OF A PROPERLY GROUNDED PUMP SYSTEM, FLAMMABLE LIQUIDS ARE SAFER TO HANDLE. USE THE STATIC PROTECTION KIT (SHOWN IN THIS CATALOG SHEET) WITH THIS PRODUCT.

Inlet Strainer

PART NO.	PUMP MODELS	CONSTRUCTION
A100109	TT, TB** (1-5/8" O.D.)	PVC/POLYPROPYLENE
A100111	PF, BT (2" O.D.)	316SS
A100337	TT,TB (1-1/2" O.D.)	316SS
A100855	PF (2" O.D.)	POLYPROPYLENE

**FOR USE WITH CPVC TUBE

Discharge Tubing

PART NO.	PUMP MODELS	CONSTRUCTION
J103470	EP	3/4" PVC
J102785	TB, TT	1" PVC
M100076	BT	1-1/2" PVC
J100302	PF	1" REINFORCED PVC

Static Protection Kit

PART NO.	PUMP MODELS
A100835	PFS, TBS, TTS,STTS
A101521*	PFS, TBS, TTS,STTS
A100836	BTS,SBTS
A100961	TMS (includes ground wire assy. only)

CONTENTS

1 - 4' GROUNDED HOSE WITH SPECIAL ENDS
1 - 6' MOTOR/TUBE GROUND WIRE WITH CLAMP AND TWO (AIR OR ELEC.) TERMINALS WITH LOCKWASHERS
1 - STAINLESS STEEL HOSE CLAMP
1 - #8-32 X 1/4 BRASS RD HD SCREW WITH #8 BRASS LOCKWASHER

*GROUNDED HOSE HAS THREADED END TO ATTACH J101929 ALUMINUM NOZZLE

NOTE: SPECIAL HOSE LENGTHS AVAILABLE UPON REQUEST

2" IPS Drum Adapter

PART NO.	PUMP MODELS	CONSTRUCTION
M100088	BT, PF, TM	GALVANIZED STEEL
M100089	TT, TB*	GALVANIZED STEEL
M100090	TT, TB*	POLYPROPYLENE
M100091	TT, TB**	POLYPROPYLENE
M100092	TT, TB*	316SS
M100094	BT, PF, TM	316SS
M100095	BT, PF, TM	POLYPROPYLENE
J100366	EP	POLYPROPYLENE

*FOR USE WITH STAINLESS STEEL TUBE
**FOR USE WITH CPVC TUBE

Wall Mount Bracket

PART NO.	PUMP MODELS
M100015	TB, PF, TT, TM, BT-1, BT-2
M100740	BT-3

Filter Lubricator

FILTER LUBRICATOR ASSEMBLY

PART NO.	MOTOR MODELS
A100003	M2, M6, M6X, M18,
A100221	M19, M20

15' AIR HOSE

PART NO.	MOTOR MODELS
A100009	M2, M6, M6X, M18
J100243	M19, M20

FINISH THOMPSON INC.
921 Greengarden Road • Erie, PA 16501-1591 U.S.A.
Ph 814-455-4478 • Fax 814-455-8518
Email fti@finishthompson.com • www.finishthompson.com

Toll Free USA & Canada 1-800-834-9384
Literature ID No. FT95-566D, 9-03

QUALITY PRECISION & PRIDE
AN ISO 9001 COMPANY