



Totally Versatile High Pressure Cleaning System

- Proven dependability of the CAT PUMP ceramic SF Plunger Pump offers unequaled performance life in its horsepower range.
- Custom designed, American made industrial electric motor features a thermal overload protection with reset and low amp draw performance.
- A 35 foot electrical cord features a Ground-Fault Circuit-Interrupter for protection and maximum safety during operation.
- A convenient Pop-Up cord wrap makes carrying and storing easy and neat.
- Versatile Vari-Nozzle features low to high pressure adjustment as well as 0° to 60° spray angle adjustment for low pressure chemical application and high pressure rinse.
- Adjustable pressure regulating Unloader permits the setting and maintaining of system pressure.
- Chemical Injector with inlet hose and chemical strainer permits chemical and cleaning solution application at operator selected intensity.
- Dual Pressure Switches with mechanical relay on "Hi-Temp units" shuts unit off when trigger gun is released or when there is insufficient flow to the inlet of the unit.
- Safety By-Pass Hose with Thermo Valve on "standard units" minimizes excessive liquid heat build-up during "intermittent" non-use.
- Lightweight Shut-off Gun with insulated lance and quick coupler allows easy assembly and quick changes to the many standard or optional accessories.
- Easy-to-read glycerine filled Pressure Gauge permits pressure adjustments to meet exact spraying or cleaning needs and the monitoring of system performance.
- A 30 ft. high performance Hose with swivel and quick disconnect for ease in operation and assembly.
- High impact molded plastic case is extremely durable, lightweight and compact (22x17x10").



"Customer confidence is our greatest asset"

Quick coupled accessories expand your cleaning capabilities



Rotating Brush with extension has gentle nylon bristles to agitate stubborn stains and dirt before blasting with high pressure.



Jetter Hose allows tight radius bend or effective pipe and tube cleaning (30 ft. or 50 ft.). Special stainless steel **Tri-Jet Nozzle** designed to deliver a three directional blasting spray.



Sandblaster with extension, probe and 15 ft. hose provides discharge line induction of sand, fertilizer, grass seed and other granular substances for special surface treatment or injection.

Organize your work

Industrial cart offers convenient transporting and storing. Two-wheel heavy-duty construction with chemical rack, gun holder and bottom rack for TUFF CAT cleaning unit.

Wall Mount for conversion to stationary, out-of-the-way operation and convenient storage.

Chemical Rack will hold 3 (1-gal.) or 2 (2.5-gal.) chemical containers to keep cleaning solutions close to the task.



Choose the TUFF CAT that's right for you

MODEL	Standard	Pulsator	High Temp	Pressure PSI	Flow GPM	Inlet Pressure PSI	Maximum Liquid Temperature	Hp	Voltage	Hz	Maximum Amps	Weight lbs.
2X1000*	x			1000	2.0	Flooded to 75	145°F	1.5	110 to 115V	60	15	60
2X1000P		x		1000	2.0	Flooded to 75	145°F	1.5	110 to 115V	60	15	60
2X1000HT			x	1000	2.0	30-75	190°F	1.5	110 to 115V	60	15	60
2X1000HTP		x	x	1000	2.0	30-75	190°F	1.5	110 to 115V	60	15	60
2X1500	x			1500	2.0	Flooded to 75	145°F	2	110 to 115V	60	20	73
2X1500HT			x	1500	2.0	30-75	190°F	2	110 to 115V	60	20	73
2X1500HTP		x	x	1500	2.0	30-75	190°F	2	110 to 115V	60	20	73
2X2000HT			x	2000	2.2	30-75	190°F	3	208 to 230V	60	14	79
3X1000	x			1000	3.0	Flooded to 75	145°F	2	110 to 115V	60	20	73
3X1000P		x		1000	3.0	Flooded to 75	145°F	2	110 to 115V	60	20	73
3X1000HT			x	1000	3.0	30-75	190°F	2	110 to 115V	60	20	73
3X1000HTP		x	x	1000	3.0	30-75	190°F	2	110 to 115V	60	20	73
3X1500HT			x	1500	3.0	30-75	190°F	3	208 to 230V	60	14	79
3X1500HTP		x	x	1500	3.0	30-75	190°F	3	208 to 230V	60	14	79
3X1250	x			1000	2.4	Flooded to 75	145°F	2	220V	50	10.2	73

*UL, CSA listed.

Products described hereon are covered by one or more of the following U.S. patents 3558244, 3652188, 3809508, 3920356, 3930756 and 5035580

World Headquarters

CAT PUMPS

1681 - 94th Lane N.E. Minneapolis, MN 55449-4324

Phone (763) 780-5440 — FAX (763) 780-2958

e-mail: sales@catpumps.com

www.catpumps.com

International Inquiries

FAX (763) 785-4329

e-mail: intl@catpumps.com



"The World's Most Dependable Pumps"

CAT PUMPS (U.K.) LTD.

1 Fleet Business Park, Sandy Lane, Church Crookham, Fleet

Hampshire GU52 8BF, England

Phone Fleet 44 1252-622031 — Fax 44 1252-626655

e-mail: sales@catpumps.co.uk

N.V. CAT PUMPS INTERNATIONAL S.A.

Heiveldekens 6A, 2550 Kontich, Belgium

Phone 32-3-450.71.50 — Fax 32-3-450.71.51

e-mail: cpi@catpumps.be www.catpumps.be

CAT PUMPS DEUTSCHLAND GmbH

Buchwiese 2, D-65510 Idstein, Germany

Phone 49 6126-9303 0 — Fax 49 6126-9303 33

e-mail: catpumps@t-online.de www.catpumps.de