

Thermoplastic Sprinkler Pumps



Superior Performance

At depths to water of 20' or less

Fiberglass-Reinforced Thermoplastic Pump Housing

For the highest corrosion resistance

High Capacity

Ideal for larger sprinkler zones or water transfer with 1-1/2" or 2" tapping for suction and discharge

Heavy-Duty Dual-Voltage Motor

Preset at 230V

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required, sold separately

1-Year Warranty

Includes:
Threaded ports for pressure gauge and drain plug, detailed owner's manual

2 HP 69 GPM
FP5182

1-1/2 HP 67 GPM
FP5172

1 HP 55 GPM
FP5162

PERFORMANCE																		
MODEL/UPC	HP	GPM	VOLTS	DISTANCE OF PUMP ABOVE WATER	DISCHARGE PRESSURE (PSI)										NPT PIPE SIZE		CARTON DIMS. (IN INCHES)	WT. (LBS.)
					10	15	20	25	30	35	40	45	50	SUCTION	DISCH.			
FP5182 022315100725	2	69	230/115	5'	69	64	59	53	47	40	34	24	14	2"	2"	21.563 x 12.813 x 15.375 18/PALLET	42	
				10'	67	62	56	50	45	38	30	18	7					
				15'	65	60	54	48	42	35	27	13	-					
				20'	62	57	52	46	40	32	23	10	-					
FP5172 022315100718	1-1/2	67	230/115	5'	67	66	61	55	48	39	33	18	-	1-1/2"	1-1/2"	21.813 x 12.313 x 13.125 24/PALLET	34.1	
				10'	61	58	56	52	45	37	27	14	-					
				15'	56	55	54	51	44	34	20	8	-					
				20'	46	45	44	43	37	28	11	-	-					
FP5162 022315100701	1	55	230/115	5'	55	51	45	38	31	23	17	-	-	1-1/2"	1-1/2"	21.813 x 12.313 x 13.125 24/PALLET	30.6	
				10'	49	46	42	35	28	19	13	-	-					
				15'	48	45	39	32	24	16	8	-	-					
				20'	45	44	37	29	20	11	-	-	-					

* Performance shown in gallons per minute