



LIQUID METER  
FMT 50 PP

NEW



INNOVATORS  
IN FLOW TECHNOLOGY

## NEW – FLUX LIQUID METER TYPE FMT 50 PP



The cost effective interlocked wheel impeller in the measuring chamber guarantees a fast and safe filling process. Suitable for neutral, low viscosity, not flammable liquids in conjunction with our JUNIORFLUX pump.

#### Benefits:

User-friendly handling, 5-digit LCD-Display, indication of the subset and total (not resetable), fast and safe calibration.

Type	FMT 50 PP
Flowrate	5-50 l/min
Operating pressure at 20 °C	4 bar
Viscosity	max. 40 mPas (cP)
Operating temperature	- 10 °C up to max. + 50 °C
Accuracy (not calibrated)	± 2 %
Accuracy (calibrated)	± 1 %
Inlet-outlet connections	Inlet G 1 (BSP 1"), outlet G 1A (BSP 1" male)
Material: housing	Polypropylene (PP)
Material: seal	FKM
Protection	IP 65
Weight	0,3 kg
<b>Part No.</b>	<b>A05 00 003</b>



Please ask for more information on FLUX liquid meters and details on our laboratory and barrel pump JUNIORFLUX. We would be glad to send you a detailed catalogue.



INNOVATORS IN FLOW TECHNOLOGY

**FLUX-GERÄTE GMBH**  
Talweg 12 · D-75433 Maulbronn  
Tel. 070 43/101-440 · Fax 070 43/101-444  
Fax International +49 70 43 / 1 01 -555  
info@flux-pumpen.de · www.flux-pumpen.de