

P200 Pumps



	Pump	LH/RH	DRIVE	SHAFT	BACKEND	UNLOADER	INJECTOR SIZE	THERMAL	OIL	
Pump Model	P205	0.5GPM @ 2500PSI @ 1750RPM and 0.9 GPM @ 2500 PSI @ 3450 RPM								
	P206	0.8GPM @ 2500PSI @ 1750RPM and 1.5 GPM @ 2500 PSI @ 3450 RPM								
	P207	0.9GPM @ 2500PSI @ 1750RPM and 1.7 GPM @ 2500 PSI @ 3450 RPM								
	P208	1.0GPM @ 2500PSI @ 1750RPM and 1.9 GPM @ 2500 PSI @ 3450 RPM								
	P209	1.5GPM @ 2500PSI @ 1750RPM and 2.7 GPM @ 2500 PSI @ 3450 RPM								
	P210	1.8GPM @ 2500PSI @ 1750RPM and 3.3 GPM @ 2500 PSI @ 3450 RPM								
	P211	2.1GPM @ 2500PSI @ 1750RPM and 3.8 GPM @ 2500 PSI @ 3450 RPM								
	P225	0.9GPM @ 3000PSI @ 1750RPM and 1.6 GPM @ 3000 PSI @ 3450 RPM								
	P226	1.5GPM @ 3000PSI @ 1750RPM and 2.8 GPM @ 3000 PSI @ 3450 RPM								
	P223	1.6GPM @ 3000PSI @ 1750RPM and 3.0 GPM @ 3000 PSI @ 3450 RPM								
	P228	1.8GPM @ 3000PSI @ 1750RPM and 3.35 GPM @ 2500 PSI @ 3450 RPM								
	P230	1.1GPM @ 2500PSI @ 1750RPM and 2.05 GPM @ 2500 PSI @ 3450 RPM								
	P217	1.8GPM @ 2500PSI @ 1750RPM and 3.3 GPM @ 2500 PSI @ 3450 RPM								
	P227	2.1GPM @ 2500PSI @ 1750RPM and 3.8 GPM @ 2500 PSI @ 3450 RPM								
	P221	2.34GPM @ 2500PSI @ 1750RPM and 4.2 GPM @ 2000 PSI @ 3450 RPM								
P218	3.4GPM @ 2500PSI @ 1750RPM									
P219	4.2GPM @ 2500PSI @ 1750RPM									
P220	4.7GPM @ 2500PSI @ 1450RPM and 4.7 GPM @ 2000 PSI @ 1750 RPM									
Shaft Side	LH Shaft	L								
	RH Shaft	R								
Electric Motor	(56C) 5 7/8" or 5.11" dia.	E1		(1)1155 / (4)1176A-1 / (4)1176-2 (Ass. Parts 06773, (4)7435)						
	(TC Face) 7 1/4" dia. Bolts	E2		(1)6495 / (4)1176A-1 / (4)1176-2 (Ass. Parts 06773, (4)7803)						
Gas Motor	(Under 9HP) 3-5/8" dia. Bolts	G1		(1)1155 / (4)1176A-1 / (4)1176-2 (Ass. Parts 06773, (4)7435 & (1)9103)						
	(9HP & More) 6.5" dia. Bolts	G2		(1)6478 / (4)1176A-1 / (4)1176-2 (Ass. Parts 06773, (4)7804 & (4)13129						
	(9HP & More) 6.5" dia. Bolts	B1		(1)8499A & (4)13445 if needed						
Coupler Size	5/8" Aluminum = 6505-0.6	B		(1) 6299 AND (1) 6332 with Each Aluminum Coupler ***** (1) 6332 with each plastic coupler						
	5/8" Delrin = 8494P	I								
	3/4" Aluminum = 6505-0.7	C								
	3/4" Delrin = 8496P	J								
	7/8" Aluminum = 6505-0.8	D								
	24mm Aluminum = 6505-24	M								
	1" Aluminum = 6505-1.0	E								
	1" Delrin = 8485P	K								
	1 1/8" Aluminum = 6505-1.1	F								
	1 1/8" Delrin = 8487P	L								
Backend	Extended	8302-L(P200)		(4)1196 / (4)1176-2						
	Short Backend	8302(P200)		X		(4)7188 / (4)1176-2				
Unloader/Regulator	No Unloader/Regulator			U or R		For Regulators, add "R"				
	Unloader/Regulator	23710 (P200)		US or RS		For Regulators, add "R"				
	Unloader (Side of Shaft)	23710 (P200)								
Siphon Injector	1.8mm (Fixed)			23750-1.8		2				
	2.1mm (Fixed)			23750-2.1		3				
	2.3mm (Fixed)			23750-2.3		4				
	1.8mm (Adjustable)			23750-1.8A		6				
	2.1mm (Adjustable)			23750-2.1A		7				
	2.3mm (Adjustable)			23750-2.3A		8				
Thermal	Thermal (Blank if No Thermal Relief Valve)						23422A (1/2")		T	
Oil	7.5 ounces for short gear ends / 9.0 ounces for long gear ends								O	
NOTE: Pumps without Bell Housing to include (1)1067 Associated parts										
Method: Follow "shaded" boxes to follow the part number. Corresponding items included, next to the box.										