

# EAGLE LINE NUMBERING CHART

## P300 SERIES



	Pump	LH/RH	DRIVE	SHAFT	BACKEND	UNLOADER	INJECTOR SIZE	THERMAL	OIL
Pump Model	P317	3.5GPM @ 3000PSI @ 1750RPM and 3.5GPM @ 3300PSI @ 1750RPM							
	P323	3.5GPM @ 3300PSI @ 1750RPM and 3.5GPM @ 3630PSI @ 1750RPM							
	P340	3.9GPM @ 3500PSI @ 1750RPM and 3.9GPM @ 4000PSI @ 1750RPM							
	P316	4.1GPM @ 3000PSI @ 1450RPM and 5.0 GPM @ 2750 PSI @ 1750 RPM							
	P322	4.1GPM @ 3300PSI @ 1450RPM and 5.0 GPM @ 3025 PSI @ 1750 RPM							
	P326	4.1GPM @ 3500PSI @ 3450RPM							
	P314	4.4GPM @ 3500PSI @ 3450RPM and 4.4 GPM @ 4000 PSI @ 3450 RPM							
	P321	4.4GPM @ 3200PSI @ 3450RPM and 4.4 GPM @ 3500 PSI @ 3450 RPM							
	P318	5.1GPM @ 2000PSI @ 1450RPM and 6.2GPM @ 1000 PSI @ 1750 RPM							
	P324	5.1GPM @ 2200PSI @ 1450RPM and 6.2GPM @ 1100 PSI @ 1750 RPM							
	P319	5.2GPM @ 2500PSI @ 3450RPM and 5.2GPM @ 2700 PSI @ 3450 RPM							
P325	5.2GPM @ 2750PSI @ 3450RPM and 5.2GPM @ 3025 PSI @ 3450 RPM								
Shaft Side	LH Shaft	L							
	RH Shaft	R							
Electric Motor	(56C) 5 7/8" or 5.11" dia.	E1		(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435)					
	(TC Face) 7 1/4" dia. Bolts	E2		(1) 06495 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07803)					
Gas Motor	(Under 9HP) 3-5/8" dia. Bolts	G1		(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435 & (1) 09103)					
	(9HP & More) 6.5" dia. Bolts	G2		(1) 06478 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07804 & (1) 13129					
	(9HP & More) 6.5" dia. Bolts	B1		(1) 08499A & (4) 13445 if needed					
Coupler Size	5/8"	Aluminum = 06505-0.6	B		(1) 06299 AND (1) 06332 with Each Aluminum Coupler ***** (1) 06332 with each plastic coupler				
	5/8"	Delrin = 08494P	I						
	3/4"	Aluminum = 06505-0.7	C						
	3/4"	Delrin = 08496P	J						
	7/8"	Aluminum = 06505-0.8	D						
	24mm	Aluminum = 06505-24	M						
	1"	Aluminum = 06505-1.0	E						
	1"	Delrin = 08485P	K						
	1 1/8"	Aluminum = 06505-1.1	F						
	1 1/8"	Delrin = 08487P	L						
1 3/8"	Aluminum = 06505-1.3	H							
1 3/8"	Delrin = 08489P	N							
Backend	Extended	08410-LG (P300)				(4) 01196 / (4) 01176-2			
	Short Backend	08410B (P300)		X		(4) 07188 / (4) 01176-2			
Unloader/Regulator	No Unloader/Regulator	\							
	Unloader/Regulator	23280 (P300)		U or R		For Regulators, add "R"			
	Unloader (Side of Shaft)	23280 (P300)		US or RS		For Regulators, add "R"			
Siphon Injector	1.8mm (Fixed)			23750-1.8		2			
	2.1mm (Fixed)			23750-2.1		3			
	2.3mm (Fixed)			23750-2.3		4			
	1.8mm (Adjustable)			23750-1.8A		6			
	2.1mm (Adjustable)			23750-2.1A		7			
2.3mm (Adjustable)			23750-2.3A		8				
Thermal	Thermal (Blank if No Thermal and Pulsator Valve)					23422A (1/2")		T	
Oil	14.2 ounces for short gear ends / 17 ounces for long gear ends								O

NOTE: Pumps without Bell Housing to include (1) 01067 Associated parts

Method: Follow "shaded" boxes to follow the part number. Corresponding items included, next to the box.