

1GA & 2GA

1½" AND 2" DISCHARGE - SUBMERSIBLE GRINDER PUMPS

MOTOR DATA

Model	HP	Phase	Volts	RPM	Maximum Amps	Service Factor	Start Amps	Locked Rotor Amps	KVA Code	Full Load Motor Eff.
1GA71G1HD	2	1	230	3500	13.0	1.5	74.0	52.0	D	77.1
1GA71G1LD					22.0	1.8	120.0	100.0	E	
1GA81H1GD	3				38.0	1.88	134.0	170.0	D	79.5
2GA81H1KD					12.0	1.33	63.0	62.0	F	
2GA31J1FD	10.0				60.0		54.0			
2GA31J1JD	5				5.0		30.0	27.0		
1GA71H2CD	3	4.0	20.0		22.0					
1GA71H3CD		200	17.0		133.0	79.0				
1GA71H4CD		230	15.0		144.0	75.0				
1GA71H5CD		460	7.6		77.0	41.0				
1GA81J2BD	5	3	575		6.0	53.0	30.0	79.5		
1GA81J3BD			200		17.0	133.0	79.0			
1GA81J4BD			230		15.0	144.0	75.0			
1GA81J5BD			460		7.6	77.0	41.0			
2GA81J2ED			575		6.0	53.0	30.0			
2GA81J3ED			200		17.0	133.0	79.0			
2GA81J4ED	230		15.0		144.0	75.0				
2GA81J5ED	460		7.6		77.0	41.0				
2GA31K2AD	7½		575	6.0	53.0	30.0	G	84.5		
2GA31K3AD			200	30.0	258.0	189.0				
2GA31K4AD			230	26.0	229.0	164.0				
2GA31K5AD			460	13.0	113.0	82.0				
2GA31K2DD		575	11.0	84.0	66.0					
2GA31K3DD		200	30.0	258.0	189.0					
2GA31K4DD		230	26.0	229.0	164.0					
2GA31K5DD		460	13.0	113.0	82.0					
	575	11.0	84.0	66.0						

APPLICATION DATA

Maximum Solid Size	N/A
Minimum Casing Thickness	5/16"
Casing Corrosion Allowance	1/8"
Maximum Working Pressure	80 PSI
Maximum Submergence	65 feet
Minimum Submergence	Top of motor dome
Maximum Environmental Temperature	40°C (104°F) continuous operation

CONSTRUCTION DETAILS

Power Cable - Type	1Ø	14/7 - 2HP, 12/7 - 3HP, 8/4 & 10/3 - 5HP SUBCAB (Single Cable)
	3Ø	14/7- 3HP, 12/7- 5HP, 8/4 & 10/3 - 7.5HP SUBCAB (Single Cable)
Motor Housing	Gray Cast Iron - ASTM A48-Class 35B	
Bearing Housing	Gray Cast Iron - ASTM A48-Class 35B	
Seal Housing	Gray Cast Iron - ASTM A48-Class 35B	
Casing	Gray Cast Iron - ASTM A48-Class 35B	
Impeller	Gray Cast Iron - ASTM A48-Class 35B	
Motor Shaft	AISI 431 Stainless Steel	
Motor Design	Air filled, Permanently Lubricated, Class F Insulation	
Motor Overload Protection	Single and Three Phase require ambient compensated Class 10, quick-trip overloads in the control panel	
Float Leakage Sensor (FLS) (Seal Sensor)	Detects the presence of water in the stator chamber. Connect to a Leakage Sensor Detector Circuit containing a patented Mini CAS (Control and Status) monitoring unit mounted in the control panel.	
Motor Thermal Protection	Normally closed on-winding thermostats open at 260° F (125° C) and close at 158° F (70° C). Connect to patented Mini CAS in control panel.	
External Hardware	300 Series stainless steel	
Impeller Type	Semi-open with pump out vanes on back shroud	
Rotating Cutter	Two blades; chrome alloyed cast iron	
Cutter Ring	Hardened 316L Stainless Steel	

STANDARD PARTS

Ball Bearing - upper	Single row ball
Ball Bearing - lower	Double row angular contact ball
Mechanical Seals <i>(See Nomenclature page, 11th Character)</i>	Lower - Tungsten Carbide/Tungsten Carbide, Upper - Carbon/Ceramic
	Lower - Ceramic/Ceramic, Upper - Carbon/Ceramic
	Lower - Tungsten Carbide/Ceramic, Upper - Carbon/Ceramic
O-Ring - bearing housing	BUNA-N
O-Ring - motor housing	BUNA-N

Xylem Inc.

2881 East Bayard Street Ext., Suite A, Seneca Falls, NY 13148

Phone: (866) 325-4210 Fax: (888) 322-5877

www.xylem.com/brands/gouldswatertechnology

