

Kits include:

- CentriPro Three Phase Motor
1.5 - 5 HP, 230 V
- CentriPro Aquavar SOLO™ Controller
with Transducer
- Goulds Water Technology GS Water End
(pump)
- **Kits available for:**
 - 30-60 Hz Operation - BGPROPAK60
 - 30-80 Hz Operation - BGPROPAK80



Aquavar ProPak Kits

BRGPROPAK

 **GOULDS**
WATER TECHNOLOGY
a xylem brand

ProPak Features:

- Simple, fast sizing and installation.
- Range curves and selection charts generated from actual R&D tests.
- Kits configured for either 30-60 or 30-80 Hz maximum operation.
- Wiring is as easy as standard three-wire control box:
 - L1, L2 and Ground in from power supply
 - Red, Yellow, Black and Ground out to motor
- Pressure is factory preset at 50 psi with simple, fast, field adjustability for higher pressures.
- Three phase output to motor reduces wire cost.
- Goulds model GS features the Guardian bearing system and field proven sand and abrasive handling floating stack design.
- Switch Input for connecting a pressure switch or float switch.
- Grounding provisions for transducer and transducer cable.

ProPak kits do not include pressure tanks, order tanks separately.

Aquavar SOLO Controller Features:

New, more versatile user interface board

- Provides switch connection for optional pressure or level switch
- New current limit settings for all new CentriPro motors
- Dry well sensitivity switch
- Low pressure cut-off protection
- 5 or 20 PSI pressure drop restart switch
- Transducer better protected from transient power surges

Transducer Features:

- Large port orifice to prevent clogging
- Case to electronics surge protection
- All Stainless Steel construction
- Pressure surge capability without the use of a pressure snubber
- Case coupled noise immunity
- Reverse voltage protection
- Line to electronics ground surge protection on all lines
- Transducer cable has ground wire built-in
- Ground clamp provided for transducer to cable grounding

PROPAK PERFORMANCE RANGE AND COMPONENTS - ProPak 80 Hz

MODEL	HP	Shut-Off Head (ft)	at Best Efficiency		at Max Runout		WE	Motor	Controller	
			Flow (GPM)	TDH (ft)	Flow (GPM)	TDH (ft)				
7GP0715	1.5	665	7	480	16	110	7GS07	M15432	3AS20	
10GP0715	1.5	540	10	375	20	117	10GS07			
18GP0715	1.5	315	18	237	37	55	18GS07			
7GP1020	2	880	7	640	16	146	7GS10	M20432		
10GP1020	2	660	10	480	20	160	10GS10			
18GP1020	2	428	18	306	37	70	18GS10			
25GP1020	2	358	25	238	40	69	25GS10			
7GP1530	3	1140	7	820	16	175	7GS15	M30432		3AS30
10GP1530	3	923	10	650	20	205	10GS15			
18GP1530	3	582	18	420	37	87	18GS15			
25GP1530	3	466	25	317	40	100	25GS15			
33GP1530	3	390	33	230	60	70	33GS15			
18GP3050	5	990	18	680	37	140	18GS30	M50432	3AS50	
25GP3050	5	770	25	528	40	158	25GS30			
33GP3050	5	681	33	390	60	120	33GS30			

Order pressure tank separately, not included in kit

PROPAK PERFORMANCE RANGE AND COMPONENTS - ProPak 60 Hz

MODEL	HP	Shut-Off Head (ft)	at Best Efficiency		at Maximum Runout		WE	Motor	Controller	
			Flow (GPM)	TDH (ft)	Flow (GPM)	TDH (ft)				
7GP1515	1.5	688	7	538	10	386	7GS15	M15432	3AS20	
10GP1515	1.5	555	10	440	16	239	10GS15			
18GP1515	1.5	348	18	255	28	126	18GS15			
5GP2020	2	1060	5	740	7.5	440	5GS20	M20432		
7GP2020	2	959	7	701	10	480	7GS20			
10GP2020	2	660	10	546	16	287	10GS20			
18GP2020	2	444	18	324	28	160	18GS20			
25GP2020	2	340	25	227	33	120	25GS20			
7GP3030	3	1200	7	890	10	615	7GS30	M30432		3AS30
10GP3030	3	876	10	700	16	368	10GS30			
13GP3030	3	662	13	519	20	250	13GS30			
18GP3030	3	605	18	422	28	215	18GS30			
25GP3030	3	464	25	310	33	165	25GS30			
33GP3030	3	405	33	260	50	75	33GS30			
18GP5050	5	960	18	712	28	365	18GS50	M50432	3AS50	
25GP5050	5	800	25	525	33	280	25GS50			
33GP5050	5	659	33	428	50	100	33GS50			



Xylem |'zīləm|

- 1) The tissue in plants that brings water upward from the roots;
- 2) a leading global water technology company.

We're 12,500 people unified in a common purpose: creating innovative solutions to meet our world's water needs. Developing new technologies that will improve the way water is used, conserved, and re-used in the future is central to our work. We move, treat, analyze, and return water to the environment, and we help people use water efficiently, in their homes, buildings, factories and farms. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise, backed by a legacy of innovation.

For more information on how Xylem can help you, go to www.xyleminc.com



Xylem Inc.
2881 East Bayard Street Ext., Suite A
Seneca Falls, NY 13148
Phone: (866) 325-4210
Fax: (888) 322-5877

www.xyleminc.com/brands/gouldswatertechnology

Goulds is a registered trademark of Goulds Pumps, Inc. and is used under license. CentriPro and Aquavar SOLO are trademarks of Xylem Inc. or one of its subsidiaries. Noryl and Lexan is a registered trademark of GE Plastic.

© 2012 Xylem Inc. BRGPROPAK March 2011