

09/00

Hy-Line & Ultima PERFORMANCE DATA SHEET



9.4409.BI

SIZE: 44

SEAL TYPES: ALL

POLISH: 0,Y

ROTORS CODE: 9



APPLICATION DATA

MAX INPUT SHAFT TORQUE (lbft) 44
 MAX SHAFT RADIAL LOAD (lb) 63
 MAX SOFT PARTICLE DIA (in) 0.4
 DISPLACEMENT (cubic in/rev) 12
 DISPLACEMENT (US gals/100revs) 5.4

PHYSICAL DATA

PUMP WEIGHT HY~LINE (lb) 44
 PUMP WEIGHT ULTIMA (lb) 55
 OIL CAPACITY (cubic in) 61
 HOLD UP VOLUME (cubic in) 11


TIGHTENING TORQUES (lbft)

END COVER BOLTS (123) 15
 ROTOR RETAINER SCREWS (HY~LINE)(59) 40
 ROTOR CASE SCREWS (52) 7
 GEAR COVER SCREWS (18) 6
 GEAR NUTS (8) 37
 ROTOR TIE ROD NUTS (ULTIMA)(26&27)15

ROTOR CLEARANCES (in)

FRONT, ROTOR TO END COVER 0.005
 RADIAL, ROTOR TO ROTOR CASE 0.008
 MESH, LOBE TO LOBE - MIN 0.008

Jabsco



USA Jabsco
 1485 Dale Way
 Costa Mesa
 CA 92628-2158

Tel: +1 714 545 8251
 Fax: +1 714 957 0609

UK Jabsco
 Bingley Road
 Hoddesdon
 Hertfordshire, EN11 0BU

Tel: +44 (0) 1992 450 145
 Fax: +44 (0) 1992 467 132

GERMANY Jabsco GmbH
 Oststraße 28
 22844 Norderstedt

Tel: +49 (0) 40 53 53 73 0
 Fax: +49 (0) 40 53 53 73 11