

09/00

Hy-Line & Ultima PERFORMANCE DATA SHEET


9.5208Z.FI

SIZE: 52

SEAL TYPES: ALL

POLISH: Z

ROTORS CODE: 8





SIZE: 52

SEAL TYPES: ALL

POLISH: Z

ROTORS CODE: 8



APPLICATION DATA

MAX INPUT SHAFT TORQUE (lbft) 110
 MAX SHAFT RADIAL LOAD (lb) 506
 MAX SOFT PARTICLE DIA (in) 0.6
 DISPLACEMENT (cubic in/rev) 16
 DISPLACEMENT (US gals/100revs) 7

PHYSICAL DATA

PUMP WEIGHT HY~LINE (lb) 70
 PUMP WEIGHT ULTIMA (lb) 85
 OIL CAPACITY (cubic in) 67
 HOLD UP VOLUME (cubic in) 28

TIGHTENING TORQUES (lbft)

END COVER BOLTS 15
 ROTOR RETAINER SCREWS (HY~LINE) 40
 ROTOR CASE SCREWS 15
 GEAR COVER SCREWS 8
 GEAR NUTS 75
 ROTOR TIE ROD NUTS (ULTIMA) 30

ROTOR CLEARANCES (in)

FRONT, ROTOR TO END COVER 0.005
 RADIAL, ROTOR TO ROTOR CASE 0.005
 MESH, LOBE TO LOBE - MIN 0.005

Jabsco



USA Jabsco
 1485 Dale Way
 Costa Mesa
 CA 92628-2158
 Tel: +1 714 545 8251
 Fax: +1 714 957 0609

UK Jabsco
 Bingley Road
 Hoddesdon
 Hertfordshire, EN11 0BU
 Tel: +44 (0) 1992 450 145
 Fax: +44 (0) 1992 467 132

GERMANY Jabsco GmbH
 Oststraße 28
 22844 Norderstedt
 Tel: +49 (0) 40 53 53 73 0
 Fax: +49 (0) 40 53 53 73 11