

VIKING COMPACT

FEATURES & BENEFITS

- Quick to install from one side of the bulkhead
- Fits industry standard aperture, even in tight spaces
- Robust pump handle and cover in-one
- Self-priming for immediate effect
- 10' 8" (3.3 m) combined lift/head
- Easy, low-cost, low-frequency maintenance
- Durable gasket for tight fit against the bulkhead
- Rattle-free design
- Polypropylene body
- All metal parts made of stainless steel
- Easy pump-action, single diaphragm design
- KlickTite™ port connectors standard
- Hose connectors can be turned in any direction
- Heavy duty non-choke valves throughout
- High flow tricuspid valve on the outlet port
- Complies with ISO 15083

Full-capacity, hand-powered bilge pump

When you need to bail water from the bilge at sea, you need to be able to rely on the pump at hand. Thanks to the Viking Compact manual bilge pump's well considered design, bailing has never been easier. Perfect for installation in tight spaces, the Viking Compact can be mounted wherever it's most appropriate.

Discover the Viking Compact manual bilge pump, combining the best aspects of simplicity, reliability and modern industrial design.

This rugged, yet sleekly designed, single-chamber diaphragm pump provides first-rate performance and is a snap to install. It can be fitted in minutes from one side of the bulkhead with just four screws, self-sealing against the surface with a durable, watertight gasket.

With the pump house recessed behind the bulkhead, only the handle is visible from the cabin or cockpit. The well-proven diaphragm design provides high pumping capacity, ensures easy pumping action and complies with ISO 15083 safety requirements.

The Viking Compact's inlet and outlet ports can be swiveled 360° and are delivered in two sizes with every pump, 1" (Ø 25 mm) and 1 1/2" (Ø 38 mm). Naturally, the Viking Compact has KlickTite™ connectors fitted as standard, literally making hose connections a snap!



Viking Compact

TECHNICAL SPECIFICATIONS

VIKING COMPACT GENERAL INFORMATION

CAPACITY	Flow at 10 kPa head and 45 strokes/min	
	1" (Ø 25 mm) connections	9.1 GPM (34.5 l/min)
	1½" (Ø 38 mm) connections	11.9 GPM (45 l/min)
BODY	Polypropylene	
COVER	ABS	
DIAPHRAGM	Nitrile rubber	
VALVES	Nitrile rubber (1 leaf and 1 tricuspid valve)	
WETTED PARTS	Polypropylene, PA66GF30 plastics and nitrile rubber	
MAX. LIFT	7 feet (2.1 meters)	
MAX. HEAD	4 feet (1.2 meters)	
COMBINED HEAD/LIFT	10.8 feet (3.3 meters)	
CONNECTION	KlickTite™ connectors for 1" (25 mm) or 1½" (38 mm) hose; both options included	
MAX. LIQUID TEMP	140°F (+60°C)	
WEIGHT	1.5 lbs (0.675 kg)	

Available models

PART NUMBER	DESCRIPTION
10-24800-01	Viking Compact dia. 1" (25 mm) and dia. 1½" (38 mm) ports



SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. The green "➤" is a trademark of SPX FLOW, Inc.

For more information, visit www.johnsonpumpmarine.com