

**HIGH SPEED**

## COMPLETE RANGE OF DIESEL TRANSFER AND REFUELLING PUMPS

UP2



UP3



UP4

UP6



UP12



Self-priming electric pumps of small dimensions with bronze gears for transferring of liquids. Pump body in nickel-plated brass and stainless steel shaft. Main applications: transfer of diesel fuel, antifreeze.

| TYPE        | PART NUMBER        | VOLTS     | SELF-PRIM. | PRESSURE | FLOW RATE | CONSUMPTION | FUSE | PORTS male |
|-------------|--------------------|-----------|------------|----------|-----------|-------------|------|------------|
| <b>UP2</b>  | <b>M164-200-12</b> | <b>12</b> | 4,9 ft     | 22 psi   | 2,6 gpm   | 2,8A ÷ 3,2A | 5A   | 3/8" NPT   |
|             | <b>M164-200-13</b> | <b>24</b> | 4,9 ft     | 22 psi   | 2,6 gpm   | 1,4A ÷ 1,6A | 3A   | 3/8" NPT   |
| <b>UP3</b>  | <b>M164-000-12</b> | <b>12</b> | 4,9 ft     | 29 psi   | 4 gpm     | 5A ÷ 6A     | 10A  | 3/8" NPT   |
| <b>UP4</b>  | <b>M164-000-13</b> | <b>24</b> | 4,9 ft     | 29 psi   | 4 gpm     | 3A ÷ 4A     | 5A   | 3/8" NPT   |
| <b>UP6</b>  | <b>M164-060-12</b> | <b>12</b> | 4,9 ft     | 29 psi   | 6,87 gpm  | 9A ÷ 11A    | 15A  | 1/2" NPT   |
|             | <b>M164-060-13</b> | <b>24</b> | 4,9 ft     | 29 psi   | 6,87 gpm  | 5A ÷ 6A     | 7,5A | 1/2" NPT   |
| <b>UP12</b> | <b>M164-300-12</b> | <b>12</b> | 13,1 ft    | 36 psi   | 10,5 gpm  | 20A         | 30A  | 1/2" NPT   |
|             | <b>M164-300-13</b> | <b>24</b> | 13,1 ft    | 36 psi   | 10,5 gpm  | 11A         | 15A  | 1/2" NPT   |