

**LOW
SPEED**

COMPLETE RANGE OF OIL TRANSFER PUMPS

UP2/OIL



UP3/OIL
UP4/OIL



UP6/OIL



UP12/OIL



Self-priming electric pumps with helical bronze gears for transferring lubricating oils and viscous liquids. Nickel-plated brass body and stainless steel shaft. Particularly suitable for draining engine sumps with the special tubes kit (OK1) and for engines lubricating operations.

| TYPE | PART NUMBER | VOLTS | SELF-PRIM. | FLOW RATE* | | | CONSUMPTION | FUSE | PORTS male |
|----------|-------------|-------|------------|------------|-----------|------------|-------------|------|------------|
| | | | | ø 1/4" | ø 5/16" | ø 15/32" | | | |
| UP2/OIL | M164-220-12 | 12 | 3,3 ft | 4,8 gph | 14,3 gph | 52,9 gph | 2,3A ÷ 2,7A | 3A | 3/8" NPT |
| | M164-220-13 | 24 | 3,3 ft | 4,8 gph | 14,3 gph | 52,9 gph | 1,1A ÷ 1,4A | 1,5A | 3/8" NPT |
| | | | | ø 1/4" | ø 5/16" | ø 9/16" | | | |
| UP3/OIL | M164-020-12 | 12 | 3,3 ft | 5,30 gph | 15,90 gph | 87,20 gph | 5,5A ÷ 6,5A | 7,5A | 3/8" NPT |
| UP4/OIL | M164-020-13 | 24 | 3,3 ft | 5,30 gph | 15,90 gph | 87,20 gph | 2,5A ÷ 3,5A | 4A | 3/8" NPT |
| | | | | ø 1/4" | ø 5/16" | ø 9/16" | | | |
| UP6/OIL | M164-080-12 | 12 | 4,9 ft | 6,60 gph | 19,82 gph | 126,82 gph | 6,5A ÷ 8,5A | 10A | 1/2" NPT |
| | M164-080-13 | 24 | 4,9 ft | 6,60 gph | 19,82 gph | 126,82 gph | 3,5A ÷ 4,5A | 7,5A | 1/2" NPT |
| | | | | ø 15/32" | ø 5/8" | | | | |
| UP12/OIL | M164-320-12 | 12 | 6,6 ft | 95 gph | 238 gph | | 11A ÷ 12A | 15A | 1/2" NPT |
| | M164-320-13 | 24 | 6,6 ft | 95 gph | 238 gph | | 5,5A ÷ 6,5A | 7,5A | 1/2" NPT |

* OIL SAE 30 AT 77°F