

**LOW  
SPEED**

## COMPLETE RANGE OF OIL TRANSFER PUMPS

UP2/OIL



UP3/OIL  
UP4/OIL



UP6/OIL



UP12/OIL



Self-priming electric pumps with helical bronze gears for transferring lubricating oils and viscous liquids. Nickel-plated brass body and stainless steel shaft. Particularly suitable for draining engine sumps with the special tubes kit (OK1) and for engines lubricating operations.

TYPE	PART NUMBER	VOLTS	SELF-PRIM.	FLOW RATE*			CONSUMPTION	FUSE	PORTS male
				ø 1/4"	ø 5/16"	ø 15/32"			
UP2/OIL	M164-220-12	12	3,3 ft	4,8 gph	14,3 gph	52,9 gph	2,3A ÷ 2,7A	3A	3/8" NPT
	M164-220-13	24	3,3 ft	4,8 gph	14,3 gph	52,9 gph	1,1A ÷ 1,4A	1,5A	3/8" NPT
				ø 1/4"	ø 5/16"	ø 9/16"			
UP3/OIL	M164-020-12	12	3,3 ft	5,30 gph	15,90 gph	87,20 gph	5,5A ÷ 6,5A	7,5A	3/8" NPT
UP4/OIL	M164-020-13	24	3,3 ft	5,30 gph	15,90 gph	87,20 gph	2,5A ÷ 3,5A	4A	3/8" NPT
				ø 1/4"	ø 5/16"	ø 9/16"			
UP6/OIL	M164-080-12	12	4,9 ft	6,60 gph	19,82 gph	126,82 gph	6,5A ÷ 8,5A	10A	1/2" NPT
	M164-080-13	24	4,9 ft	6,60 gph	19,82 gph	126,82 gph	3,5A ÷ 4,5A	7,5A	1/2" NPT
				ø 15/32"	ø 5/8"				
UP12/OIL	M164-320-12	12	6,6 ft	95 gph	238 gph		11A ÷ 12A	15A	1/2" NPT
	M164-320-13	24	6,6 ft	95 gph	238 gph		5,5A ÷ 6,5A	7,5A	1/2" NPT

\* OIL SAE 30 AT 77°F