

## OIL CHANGE SYSTEMS



OCS3/E



OCS6/E



OCS9/E

Compact oil change electronic systems for fixed boat installations. Conceived for oil fill and drain operations for all on-board uses like generators, engines, transmissions and catwalks. Their electronic control adjusts the speed of the pump according to oil viscosity/temperature and increases its speed during priming. The system automatically shuts off in case of empty tank, short circuit and after 30 minutes of operation. OCS are indicated for a perfect cleaning of all on-board areas while avoiding leaks and dispersions on the boat floor. Easy to operate and carry.

TYPE	PART NUMBER	VOLTS	SELF-PRIM.	CONNECTIONS	FLOW RATE	CONSUMPTION
<b>OCS3/E</b>	<b>M164-924-15</b>	<b>12/24</b>	4,9 ft	1/2" BSP	2,6 gpm	4A / 2A
<b>OCS6/E</b>	<b>M164-926-15</b>	<b>12/24</b>	4,9 ft	1/2" BSP	3,9 gpm	5A / 2,5A
<b>OCS9/E</b>	<b>M164-928-15</b>	<b>12/24</b>	4,9 ft	1/2" BSP	3,9 gpm	5A / 2,5A
<b>OCS9/E</b>	<b>M164-928-1H</b>	<b>110/220</b>	4,9 ft	1/2" BSP	3,9 gpm	0,6A / 0,3A