

HAND PUMPS

V-110

ROTARY HAND PUMP

The V-110 Rotary, and the L-30A Diaphragm pump are hand operated transfer pumps designed for use in 45 gallon drums with a 2" bung adaptor.

The V-110 has non-sparking brass vanes to safely pump a variety of petroleum based fluids. Pump, bronze fitted, Cap. 1 U.S.

gal. per 10 rev., furnished with handle, discharge spout 3/4" NPT male thread, 40" telescopic suction pipe and bung adapter threaded for 2" steel drum openings.

Comes with 3/4" x 8 ft neoprene hose with bent spout, all in one carton.



PETROLEUM TRANSFER PUMPS				
Model No.	Order No.	Pipe Size NPT	Ship Wt. (lbs.)	Description
ROTARY PUMPS - SLIDING BRASS VANE TYPE				
V-110	600115	3/4"	20	Hand Pump with 2" steel drum openings
V-110H	600116	3/4"	23	Hand Pump with 2" steel drum openings, and 3/4" x 8" hose
HOSE - FOR ABOVE HAND PUMPS				
V-H1P	600171	3/4" x 8"	2	Neoprene hose

L30A

HAND PUMP

The L-30A has a tough nitrile diaphragm to safely handle petroleum fuels, lubricating oils, and water based solutions.

Pump, lightweight die-cast aluminum. Cap. 10-12 GPM,

furnished complete with handle and 2" bung adapter on pump, 40" suction pipe and 8 ft. neoprene hose with straight spout, all packaged in one carton. Suction lift up to 20 ft.



DIAPHRAGM PUMPS - NITRILE RUBBER DIAPHRAGM				
Model No.	Order No.	Pipe Size NPT	Ship Wt. (lbs.)	Description
L-30A	600135	3/4"	13	Lightweight die-cast aluminum hand pump

NO. 3

CISTERN HAND PUMP

The Monarch Number 3 cistern pump with a suction lift up to 20 feet, is a hand operated

pump for providing fresh water from shallow depths to rural homes, farms and cabins.



CISTERN PUMPS - FOR PUMPING WATER				
Model No.	Order No.	Pipe Size NPT	Ship Wt. (lbs.)	Description
3	600390	1 1/4"	21	Closed spout, 3" diameter cylinder tapped for 1 1/4" NPT pipe. Will lift up to 20 ft.

V-110, L30A, NO. 3

Water Systems

Sump and Sewage

Lawn and Sprinkler

Electric Motor Driven

Engine Driven

Frame Mount

Hand Pumps

Irrigation and Industrial