

**SINGLE-CHANNEL submersible pumps highly efficient and particularly robust and reliable. Ideal for fixed installations or for continuous heavy duty use, recommended for sewage and waste water with solid impurities in building services or industrial applications.**



### RANGE OF PERFORMANCE

Flow rate up to 1600 l/min (96 m<sup>3</sup>/h)  
Head up to 24 m

### LIMITS OF USE

Depth up to 10 m  
Liquid temperature up to + 40°C  
Passage of solid bodies max Ø 50 mm for MC 15-20-30/50  
Passage of solid bodies max Ø 70 mm for MC 30/70  
For continuous duty: minimum immersion 420 mm from pump base

### CONSTRUCTION AND SAFETY STANDARDS

EN 60034-1  
IEC 34-1  
CEI 2-3



### INSTALLATION AND USE

MC SERIES PUMPS ARE MADE OF EXCEPTIONALLY ROBUST HEAVY GAUGE CAST IRON, ABRASION RESISTANT AND LONG-LASTING, WITH A **SINGLE-CHANNEL IMPELLER** WHICH CAN HANDLE LIQUIDS WITH SUSPENDED SOLIDS AND SHORT FIBRES. THEY ARE IDEAL FOR SEWAGE, WASTE AND GROUND WATER, EVEN WITH SOLIDS OR MUD, AND ARE THEREFORE RECOMMENDED FOR BUILDING OR INDUSTRIAL EFFLUENT AND DRAINAGE OF LARGE AREAS SUCH AS CAR PARKS.

**GUARANTEE 2 YEARS** subject to our general terms of sale.

### CONSTRUCTION CHARACTERISTICS

- **PUMP BODY, MOTOR CASING:** cast iron.
- **IMPELLER:** single-channel, in cast iron.
- **BASE:** stainless steel AISI 304.
- **MOTOR SHAFT:** stainless steel EN 10088-3 - 1.4057.
- **DOUBLE SEAL:** mechanical seal **silicon carbide - widia - NBR**, with oil barrier chamber and inner lip seal to protect the seal in the event of dry running.
- **MOTOR:** submersible asynchronous, 2 pole, for continuous duty.  
**MCm:** single-phase 220÷240 V - 50 Hz  
Models up to 1.5 kW have built in thermal protection  
- 2.2 kW single-phase versions have a thermal protector provided in the winding for connection to the control box.  
**MC:** three-phase 380÷415 V - 50 Hz.  
- Thermal protectors are provided in the winding for connection to the external control panel
- **INSULATION:** class F. ● **PROTECTION:** IP 68.


### STANDARD FEATURES:

- MCm** (single-phase) Float switch.  
**10m** "H07 RN-F" submersible power cable with Schuko plug.  
1.1 to 1.5 kW models are supplied with control box with capacitor and manual reset motor protector.  
2.2 kW models are supplied with control box type QES 300 MONO.
- MC** (three-phase) **10m** "H07 RN-F" neoprene power cable

### OPTIONS ON REQUEST

- ⇒ control box for three-phase pumps
- ⇒ dual voltage: 230/400 V or 400/690 V
- ⇒ single-phase versions without float switch
- ⇒ other voltages or frequency 60 Hz

**CURVES AND PERFORMANCE DATA AT n= 2900 1/min**




TYPE		POWER		Q	Flow rate															
Single-phase	Three-phase	kW	HP		m³/h	0	3	6	12	18	24	30	36	42	48	54	60	66	72	84
MCm 15/50	MC 15/50	1.1	1.5	l/min	0	50	100	200	300	400	500	600	700	800	900	1000	1100	1200	1400	1600
MCm 20/50	MC 20/50	1.5	2	H metres	16	—	14	12.5	10.5	8.5	7	5	3	1						
MCm 30/50	MC 30/50	2.2	3		18	—	16	14	12.5	10.5	9	7	5	3	1					
MCm 30/70	MC 30/70	2.2	3		24	—	22	20	18	16	14	12	10	8	6	4	2			
					13	—	—	11.5	11	10.2	9.5	8.8	8.2	7.6	6.8	6	5.3	4.8	3.2	2

Q = Flow rate H = Total manometric head

Tolerance of the performance curves according to EN ISO 9906 App. A.

**DIMENSIONS AND WEIGHTS**



TYPE		PORT DN	passage of solid bodies	DIMENSIONS mm													kg							
Single-phase	Three-phase			a	b	c	h	h1	m	n	o	d	e	p	∅	1~	3~							
MCm 15/50	MC 15/50	2 1/2"	∅ 50 mm	162	135	212	490	188	81	200	85	75	regolabile	800	800	34.0	31.8							
MCm 20/50	MC 20/50																							
MCm 30/50	MC 30/50						500/490																	
MCm 30/70	MC 30/70	3"	∅ 70 mm	180	150	240	540/530	230				85												