




# SHALLOW WELL JET PUMPS



## MODEL 2810E 3/4 HP MODEL 2805E 1/2 HP

- Maximum flow 3/4 HP 12.5 gallons per minute
- Maximum flow 1/2 HP 6.9 gallons per minute
- Superior performance at depths to water of 25' or less
- Rugged cast iron construction maximizes pump life
- 3/4 HP ready-to-install heavy-duty dual-voltage motor preset at 230 volts
- 1/2 HP ready-to-install heavy-duty dual-voltage motor preset at 115 volts
- Self-priming after pump housing is initially filled. Protects against over-heating.
- 1-1/4" NPT suction and 1" NPT discharge pipe size



### PERFORMANCE

Model	HP	Warranty	Voltage	Pressure Switch		GPM Pumped at Different Depths to Water*					Pressure Shut-off
				On	Off	5'	10'	15'	20'	25'	
2810E	3/4	1-year	115/230	30	50	12.5	11.4	10.1	8.2	6.8	70 PSI
2805E	1/2	1-year	115/230	30	50	6.9	6.0	5.3	4.5	4.0	69 PSI

\*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

### ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
2810E	0 17561 15102 7	21.688" x 10.688" x 13.563"	1.819	24	43.3 lbs.
2805E	0 17561 14102 8	21.688" x 10.688" x 13.563"	1.819	24	41.0 lbs.