




# SPRINKLER PUMP

**MODEL 3420P 2 HP**  
**MODEL 3415P 1-1/2 HP**  
**MODEL 3410P 1 HP**



- Superior performance at depths to water of 20' or less
- Fiberglass reinforced thermoplastic pump housing for the highest corrosion resistance
- Ready to install 230 volt, heavy-duty motor, see manual for 115 volt conversion
- Self priming after pump housing is initially filled, protects against overheating



### PERFORMANCE

Model	HP	Warranty	Motor Voltage	NPT Pipe Size		Distance of Pump Above Water	Discharge Pressure PSI								
				Suction	Discharge		10	15	20	25	30	35	40	45	50
3420P	2	1-year	115/230	2"	2"	5 ft.	69	64	59	53	47	40	34	24	14
						10 ft.	67	62	56	50	45	38	30	18	7
						15 ft.	65	60	54	48	42	35	27	13	—
						20 ft.	62	57	52	46	40	32	23	10	—
3415P	1-1/2	1-year	115/230	1-1/2"	1-1/2"	5 ft.	67	66	61	55	48	39	33	18	—
						10 ft.	61	58	56	52	45	37	27	14	—
						15 ft.	56	55	54	51	44	35	20	8	—
						20 ft.	46	45	44	43	37	28	11	—	—
3410P	1	1-year	115/230	1-1/2"	1-1/2"	5 ft.	55	51	45	38	31	23	17	—	—
						10 ft.	49	46	42	35	28	19	13	—	—
						15 ft.	48	45	39	32	24	16	8	—	—
						20 ft.	45	44	37	29	20	11	—	—	—

### ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
3420P	0 22315 31584 6	21.563" x 12.813" x 15.375"	2.458	18	41.2 lbs.
3415P	0 17561 91169 0	21.563" x 12.813" x 15.375"	2.458	18	35.0 lbs.
3410P	0 22315 31583 9	21.563" x 12.813" x 15.375"	2.458	18	30.6 lbs.