

DATA INSERT-LOW PRESSURE MODELS

APPLICATION

The low pressure models are intended for use where the standard model exceeds the pressure requirements of a particular system. This may be when an instantaneous water heater is used in the system or other system components which may not tolerate higher pressures.

A drop in flow, under restricted flow conditions with some increase in pump cycling, may be noted.

An accumulator tank such as the Jabsco 12573-2000. 30573-0000, or 18810-0000 can be beneficial in a restrictive plumbing system.

Models: 36800-0200 12 V 36800-0210 24 V 36900-0200 12 V 36900-0210 24 V 36950-2200 12 V 36950-2210 24 V

SPECIFICATION

Cut-in Pressure: Cut-out Pressure: 10 psi Nominal (69kPa) 20 psi Nominal (138kPa)

NOTE: Cut-out pressure will vary slightly (+4 psi) between models and, to a lesser degree, between plumbing systems.

Other specifications remain essentailly the same as the standard higher pressure model.

REPLACEMENT SWITCH

The only difference between the standard model and the low pressure model is the pressure switch (Key 13).

FOR LOW PRESSURE MODELS **ORDER SWITCH NUMBER:** 44814-1000

Jabsco



U.S.A. Jabsco 1485 Dale Way, P.O. Box 2158 Costa Mesa, CA 92628-2158 Tel: (714) 545-8251

Fax: (714) 957-0609 UNITED KINGDOM lahsco Bingley Road, Hoddesdon Hertfordshire EN11 OBU Tel: +44 (0) 1992 450145

Printed in U.S.A.

Fax: +44 (0) 1992 467132 CANADA Fluid Products Canada 55 Royal Road Guelph, Ontario N1H 1T1 Tel: (519) 821 -1900

Fax: (519) 821-2569 JAPAN NHK Jabsco Company Ltd. 3-21-10, Shin-Yokohama Kohoku-Ku, Yokohama, 222 Tel: 045-4758906

Fax: 045-475-8908 GERMANY Jabsco GmbH Oststrasse 28 22844 Norderstedt Tel: +49-40-53 53 73 -0

© Copyright 1999, ITT Industries

TUV

CERT **ISO 9001**

OUALITY SYSTEM

All Rights Reserved

Form: 43000-0539

THE PRODUCTS DESCRIBED HEREIN ARE SUBJECT TO

IS AVAILABLE FOR YOUR INSPECTION UPON REQUEST.

THE JABSCO ONE YEAR LIMITED WARRANTY, WHICH

Rev. 6/1999